

Development of a Coded Suite of Models to Explore Relevant Problems in Logistics

Santiago-Omar Caballero-Morales ^{Corresp. 1}

¹ Postgraduate Department of Logistics and Supply Chain Management, Universidad Popular Autónoma del Estado de Puebla, Puebla, Puebla, Mexico

Corresponding Author: Santiago-Omar Caballero-Morales
Email address: santiagoomar.caballero@upaep.mx

Logistics is the aspect of the supply chain which is responsible of the efficient flow and delivery of goods or services from suppliers to customers. Because a logistic system involves specialized operations such as inventory control, facility location and distribution planning, the logistic professional requires mathematical, technological and managerial skills and tools to design, adapt and improve these operations. Main research is focused on modeling and solving logistic problems through specialized tools such as integer programming and meta-heuristics methods. In practice, the use of these tools for large and complex problems requires mathematical and computational proficiency. In this context, the present work contributes with a coded suite of models to explore relevant problems by the logistic professional, undergraduate/postgraduate student and/or academic researcher. The functions of the coded suite address the following: (1) generation of test instances for routing and facility location problems with real geographical coordinates; (2) computation of Euclidean, Manhattan and geographical arc length distance metrics for routing and facility location problems; (3) simulation of non-deterministic inventory control models; (4) importing/exporting and plotting of input data and solutions for analysis and visualization by third-party platforms; and (5) designing of a nearest-neighbor meta-heuristic to provide very suitable solutions for large vehicle routing and facility location problems. This work is completed by a discussion of a case study which integrates the functions of the coded suite.

Development of a Coded Suite of Models to Explore Relevant Problems in Logistics

Santiago-Omar Caballero-Morales

Postgraduate Department of Logistics and Supply Chain Management, Universidad Popular Autonoma del Estado de Puebla, Puebla, Mexico

Corresponding author:

Santiago-Omar Caballero-Morales

Email address: santiagoomar.caballero@upaep.mx

ABSTRACT

Logistics is the aspect of the supply chain which is responsible of the efficient flow and delivery of goods or services from suppliers to customers. Because a logistic system involves specialized operations such as inventory control, facility location and distribution planning, the logistic professional requires mathematical, technological and managerial skills and tools to design, adapt and improve these operations. Main research is focused on modeling and solving logistic problems through specialized tools such as integer programming and meta-heuristics methods. In practice, the use of these tools for large and complex problems requires mathematical and computational proficiency. In this context, the present work contributes with a coded suite of models to explore relevant problems by the logistic professional, undergraduate/postgraduate student and/or academic researcher. The functions of the coded suite address the following: (1) generation of test instances for routing and facility location problems with real geographical coordinates; (2) computation of Euclidean, Manhattan and geographical arc length distance metrics for routing and facility location problems; (3) simulation of non-deterministic inventory control models; (4) importing/exporting and plotting of input data and solutions for analysis and visualization by third-party platforms; and (5) designing of a nearest-neighbor meta-heuristic to provide very suitable solutions for large vehicle routing and facility location problems. This work is completed by a discussion of a case study which integrates the functions of the coded suite.

INTRODUCTION

Research on supply chain (SC) management and logistics has been performed following quantitative (simulation, mathematical modeling and optimization) and qualitative (case study, interviews, empirical studies) approaches (Sachan A and Datta S, 2005). These approaches have been performed on the different logistic processes of the SC such as inventory control, transportation, production and distribution (Lloyd C et al., 2013; Kuczyńska-Chalada M et al., 2018). Transportation has been reported as the largest research topic in logistics (Daugherty P et al., 2017).

With the rise of Industry 4.0 (which is associated to “Internet of Things” or “SMART systems”) logistics faces the challenge to control all operations within enterprises cooperating in supply and logistic chains (Kuczyńska-Chalada M et al., 2018). In this context, the use of (a) embedded systems and (b) intelligent systems are considered as vital resources to achieve smart and autonomous flow of raw materials, work-in-process, and distribution of end products throughout the SC in accordance to human planning (Lloyd C et al., 2013; Kuczyńska-Chalada M et al., 2018).

The development of intelligent systems is based on quantitative research as it involves optimization, mathematical modeling, simulation and statistical assessment. A key resource for these tasks is the availability of specialized data for analysis and testing. Thus, research on state-of-the-art systems for transportation planning is supported by available databases of test sets (instances) such as TSPLIB (Reinelt G, 1991, 1997) for the Traveling Salesman Problem, CVRPLIB (Uchoa E et al., 2017; Oliveira D et al., 2019) for the Vehicle Routing Problem, and

SJC/p3038 sets (Chaves AA and Nogueira-Lorena LA, 2010; Nogueira-Lorena LA, 2007) for Facility Location Problems.

However, not all databases consider the different aspects of real logistics problems such as specific demand/location patterns and/or distance metrics. Also, in practice, development and implementation of specific resources and solving methods are restricted by the required technical knowledge or proficiency associated to programming platforms and mathematical modeling. As presented in (Rao K et al., 1998) the use of software programs, computer programming and spreadsheet modeling, are effective problem-solving tools within logistic education. Hence, universities have revised their programs to provide qualified logistic professionals with these tools (Ertugut R, 2011).

Currently, there is an extensive portfolio of published educational resources for the logistic professional. For example, within the field of inventory control, the use of simulation software has been used with positive results (Al-Harkan IM and Moncer H, 2007; Carotenuto P et al., 2014). For vehicle routing and facility location problems, software such as *VRP Spreadsheet Solver* and the *FLP Spreadsheet Solver* (which can solve problems with up to 200 and 300 customers respectively) (Erdogan G, 2017b,a) can be effectively used for application and teaching purposes.

While the methodological steps to use these tools are frequently reported within the respective literature (i.e., manuals, published articles), source data such as programming code and data sets is not explicitly or publicly available for sharing. Also, license restrictions regarding the implementation software avoids the use of some simulation models for commercial purposes. The high costs of some of these licenses restrict their use by freelance professionals, micro, small and medium enterprises, which have limited economic resources.

In this context, the present work describes the development of an open-source coded suite for the academic researcher and professional in logistics and supply chain management. This with the purpose of supporting the modeling and programming skills required to implement and test more advanced methods as those reported in the scientific literature and/or shared in undergraduate/postgraduate courses. Particularly, the following aspects are addressed:

- generation of test instances for routing and facility location problems with real geographical coordinates;
- computation of Euclidean, Manhattan and geographical arc length distance metrics for solving routing and facility location problems (symmetric and asymmetric metrics are considered);
- importing/exporting and plotting of input data and solutions for analysis and visualization by third-party platforms;
- simulation of non-deterministic inventory control models for assessment of supply strategies;
- designing of a nearest-neighbor meta-heuristic to provide very suitable solutions for vehicle routing and facility location problems.

As complementary material, a case study is solved with the integration of the functions of the coded suite. Implementation of the coded suite was performed through the open source programming software *GNU Octave* (Eaton JW et al., 2018). The advantage of this software is that it runs on GNU/Linux, macOS, BSD, and Windows, and it is compatible with many MATLAB scripts. Also, its language syntax makes it easily adaptable to other languages such as C++.

DEVELOPMENT OF TEST INSTANCES

The development of location data is important to test solving methods or algorithms for facility location and vehicle routing problems. To generate location data associated to real geographical coordinates the first step is to understand the coordinate system of the real world. Figure 1 presents the ranges for longitude and latitude coordinates (λ and ϕ respectively) of the world map.




Figure 1. World map displaying the range for longitude (λ) and latitude (ϕ) coordinates in degrees.

96 With these ranges the second step consists on generating location data within specific regions.
 97 In example, consider the region delimited by $\lambda \in [-102, -100]$ and $\phi \in [20, 22]$. A set of locations
 98 within this region can be generated through two approaches:

- First, by adapting an already existing set of locations (standard test instance). There are available different sets of test instances for research within the distribution field. However, many of them are not adjusted to geographic coordinates. This can affect the process to estimate distance metrics in kilometers. Figure 2 presents the visualization of coordinates from the instance *d493* of the database TSPLIB (Reinelt G, 1997). As presented, the range of the x and y axes are different from those presented in Figure 1. These non-geographical coordinates can be converted by using the following equation:

$$v' = \left(\frac{max_{new} - min_{new}}{max_{old} - min_{old}} \right) \times (v - max_{old}) + max_{new}, \quad (1)$$

99 where v is the value within the old range and v' is the converted value within the new
 100 range. Eq. (1) is computed by the function *rescaling* of the coded suite. As presented in
 101 Figure 2 the location data from the instance *d493* is correctly converted into geographic
 102 coordinates.

- Second, by using a probability distribution. In this case, random coordinates can be generated by using distributions such as the *uniform* distribution with parameters a and b which represent the minimum and maximum values for the generation range, or the *normal* distribution where a and b represent the mean and standard deviation values within the generation range. Figure 3 presents $N=493$ geographic coordinates considering these distributions. This data was generated by the function *generatedata* of the coded suite.

109 In addition to location data, information regarding demands of locations and capacities of
 110 vehicles and warehouses must be generated for routing and coverage problems. By assuming




Figure 2. Coded Suite: Re-scaling and plotting of existing location data with the function *rescaling*.




Figure 3. Coded Suite: generation of N geographic coordinates and plotting with the function *generatedata*. (A) Data generated with *uniform* distribution ($a=-102$ and $b=-100$ for longitude, $a=20$ and $b=22$ for latitude). (B)-(E) Data generated with *normal* distribution with mean values $a = -101$ and $a = 21$ for longitude and latitude respectively. Variability of standard deviation is represented by $b = 2z$ and $b = z$ for longitude and latitude respectively, where z varies from ± 0.5 to ± 3.0 and represents the number of standard deviations for dispersion.

111 a homogeneous fleet / set of warehouses a unique value is assigned to each of these elements.
 112 However, this does not necessarily apply to the demands of the locations to be served. Some
 113 instances have considered homogeneous demand (same value for all locations). However, in
 114 practice, this is not considered. The function *rescaling* includes additional code to generate
 115 random demand for each location. Note that, within the demand context, the first location is
 116 considered to be the central depot or warehouse, thus, demand is equal to zero.

117 **A Note on the Current Approach to Generate Geographic Data**

118 While test location data is generated by mathematical methods such as in (Diaz-Parra O
 119 et al., 2017), in recent years, obtaining geographic location data, also known as geo-location
 120 data, has been facilitated by the use of smart phones with integrated GPS (Global Positioning
 121 System) receivers. In the market there are diverse SDKs (Software Development Kits) and APIs
 122 (Application Programming Interfaces) to process this data for mapping, route planning and
 123 emergency tracking purposes. Among these, the Google Maps© and ArcGIS© systems can be
 124 mentioned (Google LLC, 2020; Environmental Systems Research Institute (ESRI), 2020).

125 As geo-location data is mainly obtained from smart phones and other mobile devices used
 126 by people and organizations, using and sharing this data by developers of GIS (Geographic

Information System) applications has been the subject of debate and discussion. This is due to concerns regarding the privacy and confidentiality of this data (Richardson D, 2019; Blatt A.J, 2012). Although security technology and government regulations are frequently developed and established to ensure the ethical use of geo-location data, publicly available databases are the main resource for academic and research purposes. Recently, more benchmark instances are generated for vehicle routing problems (Uchoa E et al., 2017) which can be adapted to geographic data with the coded suite.

Nevertheless, within the context of Industry 4.0, the computational proficiency on GIS applications may become an important requirement and advantage for future logistic professionals and/or academics.

DISTANCE METRICS

Within distribution problems, a metric to determine the suitability of a route over other routes is required. The most common criteria to optimize distribution problems is to minimize the metric of distance which is positively associated to transportation costs. There is a wide set of distance metrics, being the *Euclidean* distance the most commonly used. Other metrics, such as *Manhattan* distance or *arc length* are more closely associated to real-world contexts (Reinelt G, 1997). Figure 4 presents the widely known mathematical formulations to compute these distance metrics.




Figure 4. Mathematical formulations to compute (A) Euclidean, (B) Manhattan, and (C) Arc length distances between two location points.

Within the coded suite, these metrics are computed by the function *distmetrics*. It is important to remember that the distance is computed between two points i and j , thus, the x and y coordinates, or longitude (λ) and latitude (ϕ) coordinates, must be known in advance.

An important resource for any distribution problem is known as the distance matrix A which stores all distances between each location i and j within the distribution network. Thus, this matrix, of dimension $N \times N$ (where N is the number of locations, including the central depot) stores each d_{ij} data where $i, j = 1, \dots, N$ and $d_{ii} = d_{jj} = 0$ (the distance between each point and itself is zero). The function *distmetrics* also computes the symmetric distance matrix ($d_{ij} = d_{ji}$) for each type of metric.

By considering the converted coordinates into longitude and latitude degrees, the *Euclidean* and *Manhattan* distances provide similar values. In this regard, these values do not represent kilometers. In order to obtain a distance in kilometers, the *arc length* metric is considered. This metric considers the spherical model of the Earth's surface which has a radius of 6371 kilometers. For this, the coordinates in latitude and longitude degrees are converted into radians by a factor of $\pi/180^\circ$. This leads to a symmetrical distance matrix in kilometers.

It is important to note that an approximation of the *Manhattan* distance can be estimated in terms of the *arc length* or *Euclidean* distance by considering trigonometry and right triangles theory. By knowing the angle θ between the hypotenuse and one of the catheti, and the length or magnitude of the hypotenuse (i.e., *Euclidean* or *arc length* d_{ij}), the length of both catheti can

be estimated as:

$$c_1 = d_{ij} \times \sin(\theta), \quad (2)$$

$$c_2 = d_{ij} \times \cos(\theta). \quad (3)$$

Thus, if the *Euclidean* or *arc length* metric is available, then the *Manhattan* distance can be estimated as $c_1 + c_2$. Different estimates can be obtained based on the assumed value for θ .

Finally, an asymmetric distance matrix ($d_{ij} \neq d_{ji}$) can be computed by adjusting the function *distmetrics* to represent $d_{ji} = d_{ij} + \text{unifrnd}(0, \text{mean}(d_{ij}))$. Note that this operation modifies d_{ji} by adding to d_{ij} a random uniform value within the range from 0 to the mean value of all distances within A (although a different random value can be added).

A Note on Distance Metrics

The type of distance or cost metric is one of the main aspects of distribution problems because it is correlated to the accuracy of their solution. Diverse SDKs and APIs are currently used to estimate the asymmetric/symmetric distances and/or times between locations considering the actual urban layout and traffic conditions. Tools such as Google Maps© and Waze© perform these tasks in real-time on computers and mobile devices. Nevertheless, construction of a distance matrix may require a large number of GIS queries ($n \times n - n$) which are frequently restricted by the license terms of the SDK/API. Also, there are concerns regarding the privacy and confidentiality of this data as routing patterns are sensitive information.

Thus, mathematical formulations are considered to estimate these metrics in a more direct way for the development of methods to solve distribution problems. Among other distance metrics the following can be mentioned:

- *ellipsoidal distance*, which is the geodesic distance on the ellipsoidal Earth (Mysen E , 2012). It is based on the assumption that the ellipsoid is more representative of the Earth's true shape which is defined as *geoid*. While the spherical model assumes symmetry at each quadrant of the Earth, the ellipsoidal model assumes the associated asymmetry and the implications for route and facility location planning (Cazabal-Valencia L et al., 2016).
- *geodesic distance on Riemannian surfaces*, which in general terms can estimate different curvatures and disturbances on the Earth's surface for route and facility location planning (Tokgöz E and Trafalis T, 2017).

INVENTORY CONTROL

Inventory management is an important aspect of distribution as proper inventory levels are required to ensure the constant supply of goods. This however must comply with restrictions to avoid unnecessary costs associated to inventory supply processes.

In this regard, the term *Economic Order Quantity* (EOQ) has been used to define the optimal lot size Q which is required to minimize inventory management costs such as those associated to ordering and holding goods through the supply chain. Determination of Q may become a complex task due to the different variables involved in the inventory supply processes such as costs, delivery times, planning horizon, cycle time, stock-out costs and probabilities, service levels, demand patterns (Thinakaran N et al., 2019).

Thus, different mathematical models have been developed to determine the EOQ considering these multiple variables (Thinakaran N et al., 2019; Braglia M et al., 2019; De SK and Sana SS, 2015; Hovelaque V and Bironneau L, 2015). In this context, depending of the variability of the demand patterns (as measured by a coefficient of variability $CV = \sigma/\mu$, where σ and μ are the standard deviation and mean of the demand data respectively) there are inventory control models for deterministic and non-deterministic demand. If demand follows an almost constant pattern with small variability ($CV < 0.20$) it is assumed to be deterministic, otherwise it is non-deterministic ($CV \geq 0.20$). In practice, demand is frequently non-deterministic, and two of the most useful inventory control models for this case are the continuous and periodic review models. These models, also known as the (Q, R) (Hariga M, 2009; Adamu I, 2017) and P (Lieberman G and Hillier F, 2000) models respectively, are analyzed in the following sections.

Continuous Review Model

The (Q, R) model considers the costs and variables described in Table 1.

Table 1. Parameters and variables of the (Q, R) inventory control model.

Variable	Description
C	Purchase cost per unit of product.
C_o	Order cost per lot Q .
C_h	Holding cost per unit of product in inventory.
p	Stock-out cost per unit of product.
R	Reorder point (level of inventory at which a lot of size Q must be ordered to avoid stock-out).
d	Average daily demand of products, or average demand of products on the smallest unit of time.
σ	Standard deviation of the average daily demand of products (it must be estimated on the same unit of time as d).
μ_{LT}	Average demand of products through the Lead Time (LT). It can be estimated as $d \times LT$ if both are on the same unit of time.
σ_{LT}	Standard deviation of products through the LT . It can be estimated as $\sigma \times \sqrt{LT}$ if both are on the same unit of time.
D	Cumulative demand through the planning horizon. If d is a weekly demand, then $D = K \times d$ where K is the number of weeks within the planning horizon.
$L(z)$	Loss function associated to R .

With these parameters and variables, lots of size Q are ordered through a planning horizon to serve a cumulative demand. Figure 5 presents an overview of the supply patterns considered by this model and its mathematical formulation to determine Q , R , and the *Total Inventory Costs* associated to it. As presented, at the beginning of the planning horizon, the inventory level starts at $R + Q$. This is decreased by the daily or weekly demand estimated as d . If historical demand data is available, it can be used to provide a better estimate for d . As soon as the inventory level reaches R , the inventory manager must request an order of size Q because there is only stock to supply LT days or weeks. Here, it is important to observe that the inventory must be continuously reviewed or checked to accurately detect the re-order point R and reduce the stock-out risk during the LT .

Because uncertain demand is assumed, the inventory consumption rate is different throughout the planning horizon. Hence, R can be reached at different times. This leads to inventory cycles T of different length.

For this model, the function *continuousreview* computes the lot size Q , the reorder point R , and the *Total Inventory Cost*. This function also generates random demand test data (d_{test}) to plot the inventory supply patterns obtained with the computed parameters Q and R . d_{test} is generated through the expression:

$$d_{test} = d \pm w\sigma, \quad (4)$$

where w is the number of standard deviations and it is randomly generated within a specific range. Note that Q and R are estimated from historical data (d , σ) and an specific z as computed by the iterative algorithm described in Figure 5(B). Thus, if test data is generated with a higher variability (i.e., with $w > z$) the model can provide an useful simulation to determine the break point of the strategy determined by Q and R . Figure 6 presents examples considering $w \in [-3, +3]$, $w \in [-5, +5]$, and $w \in [-7, +7]$ for a case with $d = 10$ and $\sigma = 4$ ($CV=0.40$). As presented, by considering demand with the mathematical limit of $[-3, +3]$ standard deviations (as defined by the standard normal distribution) the model is able to avoid stock-out events. However, if much higher variability is considered (by far, higher than the input data for estimation of Q and R), the parameters of the model are not able to avoid stock-out events. Also note that, as variability increases the consumption rate is faster, thus more orders must be requested. Thus,




Figure 6. Coded Suite: Performance of the Continuous Review (Q, R) strategy with different variability conditions as computed by the function *continuousreview*. (A) Test demand data generated with $w \in [-3, +3]$ standard deviations. (B) Test demand data generated with $w \in [-5, +5]$ standard deviations. (C) Test demand data generated with $w \in [-7, +7]$ standard deviations.

patterns obtained with the computed parameter Q . As in the case of the (Q, R) model, Figure 8 presents examples considering $w \in [-3, +3]$, $w \in [-5, +5]$, and $w \in [-7, +7]$ for the variable demand rate.

Here, the advantages of the (Q, R) model are evident for demand with high variability. At the moment of review (at the end of T), the lot size $Q - I$ is estimated based on the historical data modeled through d and σ . This lot size must be able to cover the demand for the next period $T + LT$. However, this increases the stock out risk because ordering is restricted to be performed just at the end of T . Thus, if during that period the demand significantly increases (more than that modeled by σ), inventory can be consumed at a higher rate. For the considered example, the required service level was set to 98.5%. By assuming normality, the z -value associated to this probability is approximately 2.17. Thus, for demand with $w \in [-3, +3]$ standard deviations, the Q estimated by the P model is marginally able to keep the supply without stock-out. As presented in Figure 8, with higher variability there are more stock-out events. Thus, it is recommended to re-estimate the Q parameter considering the updated demand patterns during the previous $T + LT$ (i.e., update d and σ). These observations are important while evaluating inventory supply strategies.

A Note on Inventory Control Models

The analysis of the (Q, R) and P models provide the basics to understand most advanced models as they introduce the following key features: uncertain demand modeled by a probability distribution function (i.e., normal distribution), quantification of stock-out risks, fixed and variable review periods / inventory cycle times, cost equations as metrics to determine and




Figure 7. Periodic Review (P) Model. (A) Inventory Supply Pattern. (B) Mathematical formulation to estimate Q at each period. (C) Mathematical formulation of the Total Inventory Costs.

evaluate the optimal lot policy, and the use of iterative algorithms to determine the optimal parameters Q and R .

Extensions on these models are continuously proposed to address specific inventory planning conditions such as: Perishable Products (Muriana C, 2016; Braglia M et al., 2019), New Products (Sanchez-Vega MR et al., 2019), Seasonal Demand (Lee SH, 2018), Quantity Discounts (Darwish MA, 2008; Lee JY and Behnezhad A, 2015), Disruptions (Sevgen A, 2016), and Reduction of CO₂ Emissions (Caballero-Morales SO and Martinez-Flores JL, 2020).

By reviewing these works, the need to have a proper background on mathematical modeling (i.e., equations and heuristic algorithms) and computer programming is explicitly stated, providing support to the present work.

SOLVING METHODS FOR ROUTING AND FACILITY LOCATION PROBLEMS

Standard approaches of Operations Research (OR) such as Mixed Integer Linear Programming (MILP) or Dynamic Programming (DP) are often of limited use for large problems due to excessive computation time (Zäpfel G et al., 2010). Thus, meta-heuristics have been developed to provide near-optimal solutions in reasonable time for large production and logistic problems.

As introductory meta-heuristic, this work is considering two integrated local search algorithms with the fundamentals of GRASP (Greedy Randomized Adaptive Search Procedure) and Nearest-Neighbor Search (NNS). A complete review of more complex meta-heuristics and solving methods for different vehicle routing / facility location problems can be found in (Basu S et al., 2015; Prodhon C and Prins C, 2014; Bräysy O and Gendreau M, 2005a,b).

For the development of the integrated local search algorithms it is important to identify the characteristics of the vehicle routing / facility location problems and their solutions. This is discussed in the following sections.




Figure 8. Coded Suite: Performance of the Periodic (P) strategy with different variability conditions as computed by the function *periodicreview*. (A) Test demand data generated with $w \in [-3, +3]$ standard deviations. (B) Test demand data generated with $w \in [-5, +5]$ standard deviations. (C) Test demand data generated with $w \in [-7, +7]$ standard deviations.

Vehicle Routing Problem (VRP)

In this problem, a vehicle or set of vehicles departs from a single location where a depot or distribution center is established. These vehicles serve a set of locations associated to customers/suppliers to deliver/collect items.

If each vehicle has finite capacity then the vehicle's route can only visit those customer/supplier locations whose requirements do not exceed its capacity. This leads to define multiple routes to serve unique sets of customer/supplier locations where each location can only be visited once. Optimization is focused on determining the required routes and the visiting sequence to minimize traveling distance and/or costs. Figure 9 presents an overview of the capacitated VRP (also known as CVRP).

For this work, two main tasks are considered to provide a solution: partitioning and sequencing of minimum distance. Partitioning can be applied over a single total route to obtain sub-routes served by vehicles of finite capacity. Sequencing then can be applied over a set of customer locations to determine the most suitable order to reduce traveling time/distance. This can be applied on the single total route and on each sub-route.

The coded suite includes the function *nnscvrp* which implements a nearest neighbor search (NNS) approach for the sequencing and partitioning tasks. This is performed as follows:

- first, sequencing through the nearest or closest candidate nodes within a distance “threshold” is performed. This “threshold” is computed by considering the minimum distances plus the weighted standard deviation of the distances between all nodes or locations.
- second, the total partial route obtained by the NNS sequencing is then partitioned into




Figure 9. Characteristics of the capacitated vehicle routing problem (CVRP).

capacity-restricted sub-routes by the sub-function *partitioning2*.

- third, the sub-function *randomimprovement* is executed on the total partial route obtained by the NNS sequencing, and on each sub-route generated by the function *partitioning2*. This sub-function performs exchange and flip operators on random sub-sequences and points within each route/sub-route following a GRASP scheme.

Finally, the function *nns cvrp* plots the locations, the total route, and the CVRP sub-routes for assessment purposes. Figure 10 presents the results obtained for the instance *X-n219-k73.vrp* with Euclidean distance. The instance consists of 219 nodes (i.e., 218 customer/demand locations and one central depot location) and homogeneous fleet with capacity of 3. As observed, the function *nns cvrp* defined 73 sub-routes which is the optimal number as stated in the file name of the instance.




Figure 10. Coded Suite: Solution of the NNS-GRASP meta-heuristic for the CVRP instance *X-n219-k73.vrp* as computed by the function *nns cvrp*.

An important aspect of any solving method, particularly meta-heuristics, is the assessment of its accuracy. The most frequently used metric for assessment is the % error gap, which is computed as:

$$\%e = \left(\frac{a-b}{b} \right) \times 100.0, \quad (5)$$

where a is the result obtained with the considered solving method and b is the best-known solution. For the present example, the best-known solution is 117595.0 while the described NNS algorithm achieved a solution of $a = 119162.6799$. Hence, the error gap is estimated as 1.33%, which is very close to the best-known solution. Also, this result was obtained within reasonable time (117.046165 seconds).

A Note on Solving Methods for the CVRP

The CVRP is one of the most challenging problems within the logistic field due to its NP-hard complexity and relevance to distribution performance. Thus, there are two main research contexts for the CVRP:

- Problem Modeling: within this context the following extensions can be mentioned: CVRP with two-dimensional (2D) and three-dimensional (3D) loading constraints (Wei L et al., 2018; Tao Y and Wang F, 2015), CVRP with Traffic Jams (Mandziuk Z and Swiechowski M, 2017), CVRP with Carriers (Rojas-Cuevas ID et al., 2018), VRP with Carbon Emissions (Liu XH et al., 2018), and CVRP with Alternative Delivery, Pick-Up and Time Windows (Sitek P et al., 2020).
- Problem Solving: frequently, the solving method is proposed with the model of the problem. Due to the complexity of the CVRP itself, most of the solving methods are based on meta-heuristics such as: Particle Swarm Optimization (PSO) (Hannan MA et al., 2018), Quantum Immune Algorithm (QIA) (Liu XH et al., 2018), Matheuristics (Archetti C and Speranza MG, 2014), Tabu-Search (TS) (Tao Y and Wang F, 2015) and Genetic Algorithms (GA) (Mulloorakam AT and Nidhiry NM, 2019), with hybrid methods showing better performance.

To design and test meta-heuristics, it is recommended to have basic proficiency regarding the general structure of a meta-heuristic method (i.e., construction and improvement processes) and its implementation through computer programming (i.e., coding in C++, MATLAB, Python). In this aspect, the suite code *nnsccrp* can provide both resources. More information regarding VRP models and solving methods can be found in (Toffolo TAM et al., 2019; Archetti C and Speranza MG, 2014; Baldacci R et al., 2012).

Facility Location Problem (FLP)

In this problem, it is required to determine the most suitable location for a facility or set of facilities (Multi-Facility Location Problem, MFLP) to serve a set of customers/suppliers. As in the CVRP, if capacity is considered for the facilities, multiple facilities are required to serve unique sets of customer/supplier locations where each location can only be served by a unique facility. If facilities are located at the location of minimum distance to all customers/suppliers, the MFLP is known as the capacitated Weber problem (Aras N et al., 2007). However, if facilities are located at the average locations between all customers/suppliers (i.e., at the centroids), the MFLP is known as the capacitated centered clustering problem (CCCP) (Negreiros M and Palhano A, 2006). Finally, if facilities are located at already defined median locations, the MFLP is known as the capacitated p-median problem (CPMP) (Stefanello F et al., 2015). Figure 11 presents an overview of these variations of the MFLP. It is important to observe that the feature of the locations has a direct effect on the solution.




Figure 11. Characteristics of the capacitated facility location problem (CFLP): (A) Capacitated Weber Problem. (B) Capacitated Centered Clustering Problem (CCCP). (C) Capacitated p-Median Problem (CPMP).

Facility location problems are frequently solved through clustering or classification methods. Within the coded suite, the function *nnscccp* performs a nearest neighbor search (NNS) algorithm with an appropriate capacity-restricted assignment algorithm to provide a very suitable solution. This is performed as follows:

- first, it generates a feasible initial solution through the sub-function *random_assignment*. Randomness is considered when two or more nodes are located at the same distance from a centroid, and on the initial location of the centroids. This adds flexibility to the assignment task and to the search mechanism of the NNS algorithm.
- second, the initial solution is improved through the sub-function *update_centroids_assignment*.
- third, if the solution generated by *update_centroids_assignment* complies with all restrictions and its objective function's value is better than a reference value, then it is stored as the best found solution.

When solving combinatorial problems, it is always recommended to verify the correctness of the solution. It is also recommended to know the convergence patterns of the solving algorithm. Both aspects provide insights regarding hidden mistakes in the computer code and deficiencies in the search mechanisms of the solving algorithm (e.g., fast or slow convergence to local optima). To address this issue, at each iteration of the NNS algorithm, the function *nnscccp* executes a verification and a backup routine for the best solution's value. The purpose of the backup routine is to provide data for convergence analysis.

Figure 12 presents the verified results of the function *nnscccp* for the CCCP instance *SJC1.dat* considering Euclidean distance. The instance consists of 100 nodes (i.e., 100 customer/demand locations), 10 centroids (i.e., 10 facilities to be located) and homogeneous capacity of 720.




Figure 12. Coded Suite: Solution of the NNS meta-heuristic for the CCCP instance *SJC1.dat* as computed by the function *nnscccp*: (A) Assignment of customers to centroids. (B) Convergence of best found solution.

Finally, the accuracy of this solution is assessed through Eq. (5). The NNS solution, which is plotted in Figure 12, leads to a total distance value of $a = 18043.76066$ while the best-known solution leads to $b = 17359.75$. Then, the error gap is estimated as 3.94% which is within the limit of 5.0% for the CCCP.

The consideration of randomness within the search mechanism of the NNS algorithm is common to most meta-heuristic solving methods. Convergence is dependent of this aspect, thus, assessment of meta-heuristics is performed considering different CCCP instances and multiple executions. If the coefficient of variability of results through multiple executions is within 0.20 it can be assumed that the meta-heuristic is stable. Figure 13 presents an example of this extended assessment scheme considering instances from the well-known SJC and DONI databases. After 20 executions of the meta-heuristic (as performed in (Chaves AA and Nogueira-Lorena LA, 2010, 2011)), the coefficient of variability (CV), the best, worst and average results are obtained to estimate their associated error gaps from the best-known (BK) solutions of the test instances. As observed, the CV is very small, less than 3.0% for all instances, hence the algorithm is stable. Thus, a very suitable solution can be obtained within a few executions of the algorithm, which for all instances (except *doni2*) is within the error gap of 5.0%.

Instance	N	P	BK	Executions of the NNS Algorithm										CV	Error Gap (%)		
				1	2	3	4	5	6	7	8	9	10		Average	Best	Worst
SJC1	100	10	17359.75	19108.27	19233.84	19143.14	18031.42	19123.88	19393.45	18290.98	18174.94	18208.74	19200.32	0.02	8.00	3.87	11.72
SJC2	200	15	33181.65	34453.55	34263.04	33790.98	35184.40	34532.35	33966.42	34046.24	35374.06	35105.41	34846.92	0.02	3.81	0.72	7.21
SJC3a	300	25	45366.35	51494.75	47372.43	50184.63	47203.20	48262.37	48935.47	46790.16	48520.69	51850.40	49161.28	0.03	8.50	3.14	14.29
SJC3b	300	30	40695.46	44615.34	45297.04	45737.66	42897.90	43961.01	43714.43	44092.16	44020.33	42566.97	44201.15	0.02	8.14	4.60	13.34
SJC4a	402	30	61944.85	65574.16	66041.85	67444.02	65048.20	66532.38	65065.30	63879.09	65608.26	66293.10	64655.21	0.01	6.09	3.12	8.88
SJC4b	402	40	52214.55	54734.18	56138.30	54767.02	55450.18	56601.05	56984.65	56187.81	55050.67	55194.70	57268.72	0.01	6.96	4.83	9.68
doni1	1000	6	3021.41	3183.97	3184.49	3193.70	3200.12	3096.33	3228.53	3315.32	3254.76	3185.43	3184.49	0.02	6.35	2.45	9.73
doni2	2000	6	6080.70	6450.75	6771.04	6457.37	6520.50	6565.59	6943.25	6812.66	6604.67	6890.82	6462.06	0.02	9.00	6.02	14.19
doni3	3000	8	8446.08	9386.09	9164.45	9046.35	9210.88	9222.20	9284.65	9046.58	9078.15	9521.70	8764.82	0.02	9.05	3.77	12.76
doni4	4000	10	10854.48	11343.30	11554.67	12569.50	11727.37	12145.86	12228.30	11591.12	11749.20	12064.27	11900.86	0.03	9.52	4.50	15.80
doni5	5000	12	11134.94	12134.10	11826.50	12239.01	11795.63	11778.82	12228.90	11756.23	11630.03	11991.76	11688.43	0.02	7.46	4.45	13.58
Instance	N	P	BK	Executions of the NNS Algorithm										CV	Error Gap (%)		
				11	12	13	14	15	16	17	18	19	20		Average	Best	Worst
SJC1	100	10	17359.75	18414.13	18771.68	18980.26	18920.01	18238.01	18801.80	19309.07	19110.21	18456.53	18044.67				
SJC2	200	15	33181.65	33984.90	34244.03	34194.04	33933.64	33419.28	35572.49	34591.19	34987.62	34192.40	34202.39				
SJC3a	300	25	45366.35	49957.54	50486.07	49110.78	49326.85	49819.80	50118.63	49121.94	49122.90	48504.67	49125.72				
SJC3b	300	30	40695.46	42757.81	43491.62	43258.93	45979.48	46123.80	44577.86	43476.13	42845.84	43770.52	42757.56				
SJC4a	402	30	61944.85	64684.17	66330.04	66942.44	64252.03	65602.74	66930.28	64881.96	66203.34	66084.76	66330.83				
SJC4b	402	40	52214.55	56098.36	55717.76	55381.78	55560.09	56688.00	56007.38	55433.25	57244.58	55346.98	55156.16				
doni1	1000	6	3021.41	3178.30	3289.38	3280.55	3255.53	3222.71	3285.68	3272.36	3209.67	3095.41	3150.72				
doni2	2000	6	6080.70	6716.37	6523.83	6587.83	6514.85	6514.85	6757.51	6769.05	6450.75	6446.69	6792.99				
doni3	3000	8	8446.08	9460.70	9121.97	9488.05	8788.67	9107.96	9004.30	9324.03	9316.03	9523.56	9352.43				
doni4	4000	10	10854.48	11446.71	11908.09	12536.06	11531.49	12016.75	12263.57	11809.81	11522.08	11916.93	11938.64				
doni5	5000	12	11134.94	12647.01	11733.33	11695.76	12072.83	11774.91	11937.90	11931.33	11879.98	12157.47	12410.48				

Figure 13. Extended Data for Assessment of the NNS Algorithm for CCCP.

Other assessment schemes can consider the execution time, time to best solution, and average computational times. This is specific for the assessment of new solving methods. Logistic research is continuously extended in both important fields: (a) mathematical modeling of problems, and (b) adaptation and development of new solving methods. As presented, this work can provide the basis and resources for these research fields.

A Note on Solving Methods for the MFLP

As with the CVRP, the MFLP is also of NP-hard complexity and it is very relevant to distribution performance. Main research is performed on the following contexts:

- Problem Modeling: within this context the following extensions can be mentioned: k -Balanced Center Location problem (Davoodi M, 2019), Multi-Facility Weber Problem with Polyhedral Barriers (Akyüz MH, 2017), Multi-Commodity Multi-Facility Weber Problem (Akyüz MH et al., 2013), Multi-Facility Location-Allocation Problem with Stochastic Demands (Alizadeh M et al., 2015), p -Center FLP with Disruption (Du B et al., 2020), and MFLP Models for Waste Management (Adeleke OJ and Olukanni DO, 2020).
- Problem Solving: due to the complexity of the MFLP itself, most of the solving methods are based on meta-heuristics such as: Parallel Genetic Algorithms (P-GA) (Herda M, 2017), Adaptive Biased Random-Key Genetic Algorithm (ABRKGA) (Chaves AA et al., 2018), and Spatial Optimization (Yao J and Murray AT, 2020). Most recently, the use of Game Theory concepts has been proposed such as Nash Equilibria for MFLP with competition (Pelegrin B et al., 2018).

To extend on these works, it is recommended to have basic proficiency regarding the general structure of a meta-heuristic method and its implementation through computer programming. The suite code *nnscccp* can provide both resources.

APPLICATION CASE

In this section an integrative case is presented to illustrate the application of the coded suite. This case is focused on the distribution of insulin, which is a vital product for people with chronic diseases such as pancreatic insufficiency or diabetes. This is because the main function of insulin is to regulate the concentrations of glucose and lipids in the blood stream. If there is a deficiency of insulin, the body cannot process these elements efficiently, leading to liver and kidney failure, damage to nerve cells, cognitive impairment, blindness and amputations (Olivares-Reyes JA and Arellano Plancarte A, 2008; Berlanga-Acosta J et al., 2020).

Currently, the demand of insulin is increasing due to the high levels of diabetes (type 1 and type 2) within the general population (Mora-Morales E, 2014; Tsilas CS et al., 2017). Frequently, people need different insulin prescriptions, and sometimes more than one person within a region needs insulin. This leads to variable demand patterns through the general population, and distribution must be planned accordingly to supply all demands.

To address the associated logistic problem, the following steps are considered:

- (a) Design a test instance with the two main features of the considered scenario: large demand locations within a geographic region, and demand patterns per location considering the characteristics of the distribution fleet and product. Operational costs associated to inventory management must be also designed for the considered product.
- (b) Adapt the most appropriate routing model to formulate the distribution problem with inventory control to supply the considered product within a planning horizon.
- (c) Adapt the most appropriate inventory control model to establish the distribution frequency through the planning horizon with minimization of costs.
- (d) Select an appropriate solution method for the problem and analyze the results.
- (e) Discuss on potential opportunities to improve the solution.

The details of these steps are presented in the following sections.

(a) Design the Test Instance

By using the function *generatedata* a set of 550 normally-distributed location points, were generated. Then, by using the function *rescaling* these points were located within a specific geographic region. This methodology to generate the test instance is similar to the one proposed in (Diaz-Parra O et al., 2017) for the Oil Platform Transport Problem (OPTP) which is a variant of the CVRP (Diaz-Parra O et al., 2017).

From field data, the fleet of a regional distribution center for medicines typically consists of 6-10 standardized vehicles with temperature control. For this case, an homogeneous fleet of seven vehicles was considered for the set of 550 location points, and the distribution center was located at $\lambda = -98.245678$ and $\phi = 19.056784$.

The capacity of each vehicle was defined considering the characteristics of the product which consists of a pre-filled injection pen of 3 ml with 100 UI/ml (300 insulin units per pen) with an approximate cost of $C = 20$ USD and dimensions $0.10 \times 0.20 \times 0.085 = 0.0016 \text{ m}^3$. By considering 1.0 m^3 as the capacity of the vehicle's container for insulin, its capacity in terms of the product was estimated as $1.0/0.0016 = 625$ units.

Finally, a planning horizon and reliable source data were considered to determine the demand patterns for the set of locations. The daily insulin dosage reported in (Islam-Tareq T, 2018) was considered as input data for a Monte Carlo simulation model to provide statistical data (μ = mean units, σ = standard deviation units) regarding the cumulative demand for a two-weeks planning horizon. Then, this statistical data was expressed in terms of units of products as each pen contains 300 insulin units.

For reference purposes, an example of the geographic and demand data for the test instance of 550 locations points is presented in Table 3 and Table 4 respectively. The complete data is available within the supplemental files *location_data.xlsx* and *extended_demand_data.xlsx*.

(b) Adapting the Appropriate Routing Model

Due to the characteristics of the input data, the CVRP was identified as the reference routing model. In this regard, there are variations of this model which can be applied on the application case such as the Periodic VRP (PVRP) and the Time-Windows VRP (TWVRP) (Francis PM et al., 2008). However, the standard CVRP was suitable for the application case as the distribution planning must be performed accordingly to the frequency of inventory replenishment.

By defining the CVRP as the routing model, the function *distmetrics* was used to compute the distance matrix in kilometers (*arc length*) which is the input data for the CVRP.

Table 3. Example of location data (latitude, longitude) for the application case (generated by functions *generatedata* and *rescaling*). Complete data is available within the supplemental file *location_data.xlsx*.

i	λ	ϕ	...	i	λ	ϕ
1	-98.2564	19.0307	...	501	-98.2328	19.0331
2	-98.2142	19.0379	...	502	-98.2165	19.0305
3	-98.2390	19.0366	...	503	-98.2234	19.0305
.
.
50	-98.2446	19.0198	...	550	-98.2135	19.0363

Table 4. Statistical data of units of end-product (pre-filled pens) requested by the application case: Coefficient of Variability $CV = \sigma/\mu$ (generated by Monte Carlo Simulation). Complete data is available within the supplemental file *extended_demand_data.xlsx*.

i	μ	σ	CV	...	i	μ	σ	CV
1	3	1	0.33	...	496	2	1	0.50
2	4	1	0.25	...	497	4	2	0.50
3	3	2	0.67	...	498	5	2	0.40
.
.
55	5	1	0.20	...	550	8	2	0.25

Because minimization of the inventory management costs is the main objective of the distribution scheme, the *Total Inventory Cost* of the inventory control model (see Figure 5 and Figure 7) was considered as the objective function. Particularly, the order cost C_o is associated to the logistic operations of transportation and thus, it is directly associated to route planning and data from the distance matrix.

In the following section, the integration of traveled distance (source data within the distance matrix) with C_o is described considering the appropriate inventory control model.

(c) Adapting the Appropriate Inventory Control Model

As presented in Table 4 most of the demands have significant variability as their Coefficients of Variability (CVs) are bigger than 0.20. This led to consider a non-deterministic inventory control model such as (Q, R) and P .

Because the product's distribution must be performed periodically (each two weeks) it is recommended to synchronize it with the inventory supply frequency. For this purpose, the P model (periodic review) was considered as the most appropriate model because inventory replenishment through the (Q, R) model depends of the re-order point which may be reached at different times.

The following parameters were considered to adapt the P model to estimate the net requirements for the present case: T = one period of two-weeks (15 days), and LT = one day ($1/15 = 0.07$ of one period of two-weeks). Note that under this assumption, $d = \mu$ (see Table 4) and $z = 2.1700904$ for a service level of 98.5%.

Regarding costs, C_o and C_h were estimated from the point of view of the ordering entity (i.e, drugstores, small clinics, and patients at home). Because ordering costs must cover the operating costs of the supplier which are dependent of the lot size and the service distance, C_o was estimated as:

$$C_o = d_s \times \frac{1}{d_e} \times d_j + d_p, \quad (6)$$

where d_s is the diesel cost per liter, d_e is the efficiency of the vehicle (kilometers per liter), and d_j is the cumulative distance up to the delivery point j (source data within the distance

matrix). For a standard vehicle d_e was estimated as 12 kilometers per liter and d_s as 1.10 USD per liter (based on regional costs). Because d_j is directly associated to the traveled distance, its minimization was achieved through the application of the CVRP model (see function *nnscvrp*). Then, C_h was estimated as 5.0% of C .

Table 5 presents an example of the net requirements (lot size Q) per location based on the P model considering a period between reviews of two weeks (see function *periodicreview*). These results represent the final demand data for the CVRP model. The complete data is available within the supplemental file *Q_demand_data.xlsx*.

Table 5. Demand as Lot Quantities (Q) based on the Periodic Review (P) for application case (computed by function *periodicreview*). Complete data is available within the supplemental file *Q_demand_data.xlsx*.

i	Q	i	Q	...	i	Q
1	6	51	6	...	501	5
2	7	52	8	...	502	7
3	8	53	7	...	503	11
.
.
50	8	100	7	...	550	14

(d) Solution Method and Analysis of Results

Figure 14 presents an overview of the coded suite's functions used to provide a solution for the application case. By having the test instance data, the first set of results was obtained by solving the CVRP through the function *nnscvrp*. These results consisted of seven capacity-restricted sub-routes (one for each vehicle) estimated to serve all 550 locations. These results are presented in Figure 15.




Figure 14. Methodology and functions used to provide a solution for the application case.

Then, the second set of results was obtained by computing the inventory management costs at each location (see Eq. 6) based on the visiting sequence defined by each sub-route (see Figure 15). Table 6 presents an example of the order cost (C_o) and Total Inventory Cost (TC) computed at each location. The complete data is available within the supplemental file *results_inventory_costs.xlsx*.

From Table 6 (file *results_inventory_costs.xlsx*) the sum of all total costs associated to inventory management was computed as 1016.5939 USD, where the total order cost was computed as 470.5898 USD. This represents a significant investment even if appropriate inventory control and distribution planning is performed. Nevertheless, these results constitute the reference data for improvements which can be obtained by extending on the availability of other distribution centers. This is addressed in the following section.




Figure 15. Results of the distribution model as computed by the function *nnscvrp*. (A) Sub-routes. (B) Visualization of sub-routes.

Table 6. Results of the inventory control model concerning C_o and *Total Cost (TC)* as computed by the function *periodicreview*. Complete data is available within the supplemental file *results_inventory_costs.xlsx*.

i	C_o	TC	...	i	C_o	TC
1	1.2	1.96	...	496	0.4	1.05
2	1.0	1.89	...	497	0.4	1.74
3	0.7	1.88	...	498	1.0	2.42
.
.
55	0.8	1.75	...	550	1.2	2.86

(e) Opportunities for Improvement

From the previous results, the task of finding an alternative location for the distribution center (or distribution centers) was explored. First, a new location for the current distribution center was explored. By using the function *nnscvcp* a new location was estimated at $\lambda = -98.2266$ and $\phi = 19.0369$. Then, the CVRP was solved through the function *nnscvrp* and the inventory management costs associated to each sub-route were computed. For this new

location scenario, Table 7 presents an example of the order cost (C_o) and Total Inventory Cost (TC) computed at each location. The complete data is available within the supplemental file *results_inventory_costs_relocated_center.xlsx*.

Table 7. Results of the inventory control model concerning C_o and *Total Cost* (TC) as computed by the function *periodicreview* with a new distribution center located by the function *nnscvcp* (sub-routes estimated by function *nnscvcp*). Complete data is available within the supplemental file *results_inventory_costs_relocated_center.xlsx*.

i	C_o	TC	...	i	C_o	TC
1	0.7	1.44	...	496	0.7	1.37
2	0.6	1.46	...	497	0.3	1.62
3	1.1	2.25	...	498	0.6	1.97
...
...
55	1.2	2.13	...	550	0.6	2.28

From data of Table 7 (file *results_inventory_costs_relocated_center.xlsx*), the sum of all total costs was computed as 905.1940 USD for TC , and 355.1493 USD for C_o . This represents a reduction of $(1 - 905.1940/1016.5939) \times 100.0\% = 10.958\%$ and $(1 - 355.1493/470.5898) \times 100.0\% = 24.531\%$ respectively.

By obtaining this improvement, the second step consisted on considering more distribution centers. Table 8 presents the total inventory management cost for the cases with three, four, five, six and seven distribution centers. It can be observed that there is a limit to increase the number of distribution centers to reduce the total inventory costs. A steady reduction is observed for up to five distribution centers. However, a steady increase is observed for six and seven distribution centers (which implies a vehicle per distribution center). Hence, it is important to consider that there is an optimal or near-optimal number of distribution centers to reduce the total costs associated to distance. Also, the achieved savings must compensate the investment required for this additional infrastructure within a suitable period of time.

Table 8. General results of the inventory control model concerning C_o and *Total Cost* (TC) as computed by the function *periodicreview* with three to seven distribution centers located by the function *nnscvcp* (sub-routes estimated by function *nnscvcp*).

Number of Distribution Centers	Total C_o	TC
3	297.6238	847.6685
4	290.1440	840.1887
5	279.9094	829.9540
6	282.6311	832.6758
7	309.5225	859.5671

RESULTS AND CONCLUSIONS

In this work the development of resources for logistic and inventory management research was presented. These resources were complemented with source code and implementation examples to motivate their learning and application. Specifically, the following aspects were covered by this coded suite:

- development of instances for vehicle – routing/ facility location instances with near-to-real geographical data;
- development of instances with symmetric and asymmetric distance/cost data considering the main distance metrics available for modeling;
- development of exporting and plotting codes for visualization and processing by third-party platforms;

- 565 • development of implementation code to evaluate the performance of inventory management
566 techniques with uncertain demand;
- 567 • development of a nearest-neighbor search (NNS) with greedy randomized adaptive search
568 procedure (GRASP) algorithm to (1) provide very suitable solutions to integrated facility
569 location – inventory - vehicle routing problems, and (2) provide insights regarding how
570 these solving methods work. This meta-heuristic could provide very suitable results for
571 large CVRP and CCCP instances (> 300 customers/locations);
- 572 • solution and analysis of an integrative problem with the main functions of the coded suite.

573 It is important to mention that logistic research extends to many fields and problems, and
574 these resources just represent a small fraction of them. Also, the developed codes are subject to
575 improvements and thus, they can be extended in the following aspects:

- 576 • integrate the use of public GIS data through the limited free service of *Bing Maps* and
577 *Google Maps* as performed by (Erdogan G, 2017b,a);
- 578 • integrate other meta-heuristics such as Tabu-Search (TS) and Ant-Colony Optimization
579 (ACO) for a parallel execution of solving methods;
- 580 • integrate logistic problems with non-linear objective functions.

581 As introductory work, the present coded suite can provide the academic or professional with
582 the key aspects to understand most of the associated works and tools reported in the specialized
583 literature.

584 STATEMENT

585 “The author declares that there is no conflict of interest regarding the publication of this paper.”

586 REFERENCES

- 587 Adamu I (2017). Reorder quantities for (Q,R) inventory models. *International Mathematical*
588 *Forum*, 12(11):505–514.
- 589 Adeleke OJ and Olukanni DO (2020). Facility Location Problems: Models, Techniques, and
590 Applications in Waste Management. *Recycling*, 5(10):1—20.
- 591 Akyüz MH (2017). The capacitated multi-facility Weber problem with polyhedral barriers:
592 Efficient heuristic methods. *Computers & Operations Research*, 113:221–240.
- 593 Akyüz MH, Öncan T, and Altinel K (2013). Beam search heuristics for the single and multi-
594 commodity capacitated Multi-facility Weber Problems. *Computers & Operations Research*,
595 40(12):3056–3068.
- 596 Al-Harkan IM and Moncer H (2007). A simulation optimization solution to the inventory
597 continuous review problem with lot size dependent lead time. *Arabian Journal for Science*
598 *and Engineering*, 32(2):327–338.
- 599 Alizadeh M, Mahdavi I, Mahdavi-Amiri N, and Shiripour S (2015). A capacitated location-
600 allocation problem with stochastic demands using sub-sources: An empirical study. *Applied*
601 *Soft Computing*, 34:551–571.
- 602 Aras N, Yumusak S, and Altmel K (2007). Solving the capacitated multi-facility weber problem
603 by simulated annealing, threshold accepting and genetic algorithms. In Doerner, K, Gendreau
604 M, Greistorfer P, Gutjahr W, Hartl R, and Reimann M, editors, *Metaheuristics: Progress in*
605 *Complex Systems Optimization*, pages 491–112.
- 606 Archetti C and Speranza MG (2014). A survey on matheuristics for routing problems. *EURO*
607 *Journal on Computational Optimization*, 2:223—246.
- 608 Baldacci R, Mingozzi A, and Roberti R (2012). Recent exact algorithms for solving the vehicle
609 routing problem under capacity and time window constraints. *European Journal of Operational*
610 *Research*, 218(1):1–6.
- 611 Basu S, Sharma M, and Ghosh P (2015). Metaheuristic applications on discrete facility location
612 problems: a survey. *OPSEARCH*, 52(3):530—561.

- 613 Berlanga-Acosta J, Mendoza-Mari Y, Rodriguez-Rodriguez N, Garcia-del-Barco-Herrera D,
614 Garcia-Ojalvo A, Fernandez-Mayola M, Guillen-Nieto G, and Valdes-Sosa PA (2020). Burn
615 injury insulin resistance and central nervous system complications: A review. *Burns Open*,
616 4(2):41–52.
- 617 Blatt AJ (2012). Ethics and Privacy Issues in the Use of GIS. *Journal of Map & Geographic*
618 *Libraries*, 8(1):80–84.
- 619 Braglia M, Castellano D, Marrazzini L, and Song D (2019). A continuous review (Q, r) inventory
620 model for a deteriorating item with random demand and positive lead time. *Computers and*
621 *Operations Research*, 109:102–121.
- 622 Bräysy O and Gendreau M (2005a). Vehicle Routing Problem with Time Windows, Part I:
623 Route Construction and Local Search Algorithms. *Transportation Science*, 39(1):104–118.
- 624 Bräysy O and Gendreau M (2005b). Vehicle Routing Problem with Time Windows, Part II:
625 Metaheuristics. *Transportation Science*, 39(1):119–139.
- 626 Caballero-Morales SO and Martinez-Flores JL (2020). Analysis and Reduction of CO₂ Emissions
627 and Costs Associated to Inventory Replenishment Strategies with Uncertain Demand. *Polish*
628 *Journal of Environmental Studies*, 29(6):3997–4005.
- 629 Carotenuto P, Giordani S, and Zaccaro A (2014). A simulation-based approach for evaluating
630 the impact of maritime transport on the inventory levels of an oil supply chain. *Transportation*
631 *Research Procedia*, 3:710–719.
- 632 Cazabal-Valencia L, Caballero-Morales SO, and Martinez-Flores JL (2016). Logistic model for
633 the facility location problem on ellipsoids. *International Journal of Engineering Business*
634 *Management*, 8:1–9.
- 635 Chaves AA, Gonçalves JF, and Nogueira-Lorena LA (2018). Adaptive biased random-key genetic
636 algorithm with local search for the capacitated centered clustering problem. *Computers &*
637 *Industrial Engineering*, 124:331–346.
- 638 Chaves AA and Nogueira-Lorena LA (2010). Clustering search algorithm for the capacitated
639 centered clustering problem. *Computers & Operations Research*, 37(3):552–558.
- 640 Chaves AA and Nogueira-Lorena LA (2011). Hybrid evolutionary algorithm for the capacitated
641 centered clustering problem. *Expert Systems with Applications*, 38:5013–5018.
- 642 Darwish MA (2008). Joint determination of order quantity and reorder point of continuous
643 review model under quantity and freight rate discounts. *Computers & Industrial Engineering*,
644 35:3902–3917.
- 645 Daugherty P, Bolumole Y, and Schwieterman M (2017). Logistics Research: What a Long,
646 Strange Trip It's Been. *Transportation Journal*, 56(3):213–226.
- 647 Davoodi M (2019). *k*-Balanced Center Location problem: A new multi-objective facility location
648 problem. *Computers & Operations Research*, 105:68–84.
- 649 De SK and Sana SS (2015). Multi-criterion multi-attribute decision-making for an EOQ model
650 in a hesitant fuzzy environment. *Pacific Science Review A: Natural Science and Engineering*,
651 17:61–68.
- 652 Diaz-Parra O, Ruiz-Vanoye JA, Fuentes-Penna A, Bernabe-Loranca B, Perez-Ortega J, Barrera-
653 Camara RA, Velez-Diaz D, and Perez-Olguin NB (2017). Oil Platform Transport Problem
654 (OPTP) is NP-hard. *International Journal of Combinatorial Optimization Problems and*
655 *Informatics*, 8(3):2–19.
- 656 Du B, Zhou H, and Leus R (2020). A two-stage robust model for a reliable *p*-center facility
657 location problem. *Applied Mathematical Modelling*, 77(1):99–114.
- 658 Eaton JW, Bateman D, Hauberg S, and Wehbring R (2018). *GNU Octave version 4.4.0 manual:*
659 *a high-level interactive language for numerical computations*.
- 660 Environmental Systems Research Institute (ESRI) (2020). *ArcGIS*.
- 661 Erdogan G (2017a). *FLP Spreadsheet Solver*. [https://people.bath.ac.uk/ge277/flp-spreadsheet-](https://people.bath.ac.uk/ge277/flp-spreadsheet-solver/)
662 [solver/](https://people.bath.ac.uk/ge277/flp-spreadsheet-solver/).
- 663 Erdogan G (2017b). *VRP Spreadsheet Solver*. [https://people.bath.ac.uk/ge277/vrp-spreadsheet-](https://people.bath.ac.uk/ge277/vrp-spreadsheet-solver/)
664 [solver/](https://people.bath.ac.uk/ge277/vrp-spreadsheet-solver/).
- 665 Erturgut R (2011). Increasing demand for logistics technician in business world and rising
666 trend of logistics programs in higher vocational schools: Turkey case. *Procedia - Social and*
667 *Behavioral Sciences*, 15:2776–2780.

- Francis PM, Smilowitz KR, and Tzur M (2008). The Period Vehicle Routing Problem and its Extensions. In Golden et al., editor, *The Vehicle Routing Problem: Latest Advances and New Challenges*, pages 73–102.
- Google LLC (2020). *Google Maps Platform*.
- Hannan MA, Akhtar M, Begum RA, Basri H, Hussain A, and Scavino E (2018). Capacitated vehicle-routing problem model for scheduled solid waste collection and route optimization using PSO algorithm. *Waste Management*, 71:31–41.
- Hariga M (2009). A continuous review (Q,r) model with owned and rented storage facilities. In *Proc. of the IEEE International Conference on Computers & Industrial Engineering (CIE 2009)*, pages 1297–1301.
- Herda M (2017). Parallel Genetic Algorithm for Capacitated P-median Problem. *Procedia Engineering*, 192:313–317.
- Hovelaque V and Bironneau L (2015). The carbon-constrained EOQ model with carbon emission dependent demand. *International Journal of Production Economics*, 164:285–291.
- Islam-Tareq T (2018). *Fuzzy Logic: A Contemporary Technique in Refining Physicians' Prescribed Total Daily Insulin Dosage for Type 2 Diabetes Patients*. BRAC University - Department of Pharmacy, Bachelor Thesis.
- Kuczyńska-Chalada M, Furman J, and Poloczek R (2018). The challenges for logistics in the aspect of Industry 4.0. *Multidisciplinary Aspects of Production Engineering*, 1(1):553–559.
- Lee JY and Behnezhad A (2015). Incremental quantity discounts in a periodic-review stochastic inventory model with a general demand distribution. *International Journal of Mathematics in Operational Research*, 7(2):178—193.
- Lee SH (2018). *Memetic Algorithm for Stochastic Inventory Optimization with Seasonal Demand*. Erasmus University Rotterdam - Erasmus School of Economics, Master Thesis.
- Lieberman G and Hillier F (2000). *Introduction to Operations Research (7th ed.)*. McGraw-Hill.
- Liu XH, Shan MY, Zhang RL, and Zhang LH (2018). Green Vehicle Routing Optimization Based on Carbon Emission and Multiobjective Hybrid Quantum Immune Algorithm. *Mathematical Problems in Engineering*, 2018:1–10.
- Lloyd C, Pötsch T, Yi S, Zuñiga R, Safaei M, Issa S, and Rügge I (2013). Resources in logistics - a multidisciplinary challenge. In *Proc. of the 6th International Federation of Automatic Control Conference on Management and Control of Production and Logistics (IFAC 2013)*, pages 449–455.
- Mandziuk Z and Swiechowski M (2017). UCT in Capacitated Vehicle Routing Problem with traffic jams. *Information Sciences*, 406–407:42–56.
- Mora-Morales E (2014). Estado actual de la diabetes mellitus en el mundo. *Acta Medica Costarricense*, 56(2):44–46.
- Mulloorakam AT and Nidhiry NM (2019). Combined Objective Optimization for Vehicle Routing Using Genetic Algorithm. *Materials Today: Proceedings*, 11(3):891–902.
- Muriana C (2016). An EOQ model for perishable products with fixed shelf life under stochastic demand conditions. *European Journal of Operational Research*, 255(2):388–396.
- Mysen E (2012). GOCE quasigeoid performance for Norway. *International Journal of Applied Earth Observation and Geoinformation*, 35:136–139.
- Negreiros M and Palhano A (2006). The capacitated centred clustering problem. *Computers & Operations Research*, 33(6):1639—1663.
- Nogueira-Lorena LA (2007). *Problem Instances*. <http://www.lac.inpe.br/~lorena/instancias.html>.
- Olivares-Reyes JA and Arellano Plancarte A (2008). Bases moleculares de las acciones de la insulina. *Red de Revistas Científicas de America Latina, el Caribe, España y Portugal*, 27(1):9–18.
- Oliveira D, Uchoa E, Pecin D, Pessoa A, Poggi M, Vidal T, and Subramanian A (2019). *CVRPLIB Capacitated Vehicle Routing Problem Library*. <http://vrp.atd-lab.inf.puc-rio.br/index.php/en/>.
- Pelegrin B, Fernandez P, and Garcia MD (2018). Computation of Multi-facility Location Nash Equilibria on a Network Under Quantity Competition. *Networks and Spatial Economics*, 18:999—1017.
- Prodhon C and Prins C (2014). A survey of recent research on location-routing problems. *European Journal of Operational Research*, 238(1):1–17.

- 723 Rao K, Stenger A, and Wu HJ (1998). Integrating the use of computers in logistics education.
724 *International Journal of Physical Distribution & Logistics Management*, 28(4):302–319.
- 725 Reinelt G (1991). TSPLIB - A Traveling Salesman Problem Library. *ORSA Journal on*
726 *Computing*, 3(4):376–384.
- 727 Reinelt G (1997). *TSPLIB*. <http://elib.zib.de/pub/mp-testdata/tsp/tsplib/tsplib.html>.
- 728 Richardson D (2019). Dealing with Geoprivacy and Confidential Geospatial Data. *ArcNews*,
729 Spring:30–30.
- 730 Rojas-Cuevas ID, Caballero-Morales SO, Martinez-Flores JL, and Mendoza-Vazquez JR (2018).
731 Capacitated vehicle routing problem model for carriers. *Journal of Transport and Supply*
732 *Chain Management*, 12:1–9.
- 733 Sachan A and Datta S (2005). Review of supply chain management and logistics research.
734 *International Journal of Physical Distribution & Logistics Management*, 35(9):664–705.
- 735 Sanchez-Vega MR, Caballero-Morales SO, Sanchez-Partida D, and Martinez-Flores JL (2019).
736 Risk-based strategic inventory supply model for new products. In Garcia-Alcaraz et al., editor,
737 *Best Practices in Manufacturing Processes*, pages 75–95.
- 738 Sevgen A (2016). *A Continuous-Review Inventory Model with Disruptions and Reorder Point*.
739 Izmir University of Economics- Graduate School of Natural and Applied Sciences, Master
740 Thesis.
- 741 Sitek P, Wikarek J, Rutczynska-Wdowiak K, Bocewicz G, and Banaszak Z (2020). Optimization
742 of capacitated vehicle routing problem with alternative delivery, pick-up and time windows: A
743 modified hybrid approach. *Neurocomputing*, In Press:1–9.
- 744 Stefanello F, CB-de-Araújo O, and Müller F (2015). Matheuristics for the capacitated p-median
745 problem. *International Transactions in Operational Research*, 22(1):149–167.
- 746 Tao Y and Wang F (2015). An effective tabu search approach with improved loading algorithms
747 for the 3L-CVRP. *Computers & Operations Research*, 55:127–140.
- 748 Thinakaran N, Jayaprakas J, and Elanchezhian C (2019). Survey on Inventory Model of EOQ &
749 EPQ with Partial Backorder Problems. *Materials Today: Proceedings*, 16:629–635.
- 750 Toffolo TAM, Vidal T, and Wauters T (2019). Heuristics for vehicle routing problems: Sequence
751 or set optimization? *Computers & Operations Research*, 105:118–131.
- 752 Tokgöz E and Trafalis T (2017). 2-Facility manifold location routing problem. *Optimization*
753 *Letters*, 11:389–405.
- 754 Tsilas CS, de-Souza RJ, Blanco-Mejia S, Mirrahimi A, Cozma AI, Jayalath VH, Ha V, Tawfik
755 R, Di-Buono M, Jenkins AL, Leiter LA, Wolever TMS, Beyene J, Khan T, Jenkins DJA,
756 Kendall CWC, and Sievenpiper JL (2017). Relation of total sugars, fructose and sucrose with
757 incident type 2 diabetes: a systematic review and meta-analysis of prospective cohort studies.
758 *Canadian Medical Association Journal*, 189(20):711–720.
- 759 Uchoa E, Pecin D, Pessoa A, Poggi M, Vidal T, and Subramanian A (2017). New benchmark
760 instances for the Capacitated Vehicle Routing Problem. *European Journal of Operational*
761 *Research*, 257(3):845–858.
- 762 Wei L, Zhang Z, Zhang D, and Leung SCH (2018). A simulated annealing algorithm for the
763 capacitated vehicle routing problem with two-dimensional loading constraints. *European*
764 *Journal of Operational Research*, 265(3):843–859.
- 765 Yao J and Murray AT (2020). A Spatial Optimization Approach for Solving a Multi-facility
766 Location Problem with Continuously Distributed Demand. *Innovations in Urban and Regional*
767 *Systems*, pages 113–135.
- 768 Zäpfel G, Braune R, and Bögl M (2010). *Metaheuristic Search Concepts: A Tutorial with*
769 *Applications to Production and Logistics*. Springer Heidelberg Dordrecht London New York.