

A novel CAPTCHA solver framework using deep skipping Convolutional Neural Networks

Shida Lu^{Corresp., 1}, Kai Huang², Talha Meraj³, Hafiz Tayyab Rauf⁴

¹ State Grid Information & Communication Company, SMEPC, Shanghai, China

² Shanghai Shineenergy Information Technology Development Co., Ltd., Shanghai, China

³ COMSATS Institute Of Information Technology, Islamabad, Pakistan

⁴ University of Bradford, Bradford, United Kingdom

Corresponding Author: Shida Lu
Email address: lushida621@163.com

A Completely Automated Public Turing Test to tell Computers and Humans Apart (CAPTCHA) is used in web systems to secure authentication purposes; it may break using Optical Character Recognition (OCR) type methods. CAPTCHA breakers make web systems highly insecure. However, several techniques to break CAPTCHA suggest CAPTCHA designers about their designed CAPTCHA's need improvement to prevent computer vision-based malicious attacks. This research primarily used deep learning methods to break state-of-the-art CAPTCHA codes; however, the validation scheme and conventional Convolutional Neural Network (CNN) design still need more confident validation and multi-aspect covering feature schemes. Several public datasets are available of text-based CAPTCHA, including Kaggle and other dataset repositories where self-generation of CAPTCHA datasets are available. The previous studies are dataset-specific only and cannot perform well on other CAPTCHA's. Therefore, the proposed study uses two publicly available datasets of 4- and 5-character text-based CAPTCHA images to propose a CAPTCHA solver. Furthermore, the proposed study used a skip-connection-based CNN model to solve a CAPTCHA. The proposed research employed 5-folds on data that delivers 10 Different CNN models on two datasets with promising results compared to the other studies.

A novel CAPTCHA solver framework using deep skipping Convolutional Neural Networks

Shida Lu^{*1}, Kai Huang², Talha Meraj³, and Hafiz Tayyab Rauf⁴

^{*1}State Grid Information & Communication Company, SMEPC, China

²Shanghai Shineenergy Information Technology Deleloment Co., Ltd., China

³Department of Computer Science, COMSATS University Islamabad - Wah Campus, Wah Cantt 47040, Pakistan

⁴Department of Computer Science, Faculty of Engineering & Informatics, University of BRADFORD, United Kingdom

Corresponding author:

Shida Lu¹

Email address: lushida621@163.com

ABSTRACT

A Completely Automated Public Turing Test to tell Computers and Humans Apart (CAPTCHA) is used in web systems to secure authentication purposes; it may break using Optical Character Recognition (OCR) type methods. CAPTCHA breakers make web systems highly insecure. However, several techniques to break CAPTCHA suggest to CAPTCHA designers that their designed CAPTCHAs need improvement to prevent computer-vision-based malicious attacks. These existing validation schemes and conventional Convolutional Neural Network (CNN) design still need more confident validation and multi-aspect covering feature schemes to solve a CAPTCHA. This research primarily used deep learning methods to break state-of-the-art CAPTCHA using skip-connection-based multi-features covering method. Many public datasets of text-based CAPTCHAs are available, including Kaggle and other dataset repositories, where many studies also use the self-generation of CAPTCHA datasets. The previous studies are dataset-specific only and cannot perform well on other CAPTCHAs. Therefore, the proposed study uses two publicly available datasets of four- and five-character text-based CAPTCHA images to propose a CAPTCHA solver. Furthermore, the proposed research employed skip-CNN using a five-fold validation method on data that deliver ten different CNN models on two datasets, with promising results compared to the other studies.

INTRODUCTION

The first secure and fully automated mechanism, named CAPTCHA, was developed in 2000. Alta Vista first used the term CAPTCHA in 1997. It reduces spamming by 95% Baird and Popat (2002). CAPTCHA is also known as a reverse Turing test. The Turing test was the first test to distinguish human, and machine Von Ahn et al. (2003). It was developed to determine whether a user was a human or a machine. It increases efficiency against different attacks that seek websites Danchev (2014), Obimbo et al. (2013). It is said that CAPTCHA should be generic such that any human can easily interpret and solve it and difficult for machines to recognize it Bostik and Klecka (2018). To protect against robust malicious attacks, various security authentication methods have been developed Goswami et al. (2014), Priya and Karthik (2013), Azad and Jain (2013). CAPTCHA can be used for authentication in login forms, spam text reducer, e.g., in email, as a secret graphical key to log in for email. In this way, a spam-bot would not be able to recognize and log in to the email Sudarshan Soni and Bonde (2017). However, recent advancements make the CAPTCHA's designs to be at high risk where the current gaps and robustness of models that are the concern is discussed in depth (Roshanbin and Miller, 2013). Similarly, the image, text, colorful CAPTCHA's, and other types of CAPTCHA's are being attacked by various malicious attacks. However, most of them have used Deep Learning based methods to crack them due to their robustness

and confidence (Xu et al., 2020).

Many prevention strategies against malicious attacks have been adopted in recent years, such as cloud computing-based voice-processing Gao et al. (2020b,a), mathematical and logical puzzles, and text and image recognition tasks Gao et al. (2020c). Text-based authentication methods are mostly used due to their easier interpretation, and implementation Madar et al. (2017); Gheisari et al. (2021). A set of rules may define a kind of automated creation of CAPTCHA-solving tasks. It leads to easy API creation and usage for security web developers to make more mature CAPTCHAs Bursztein et al. (2014), Cruz-Perez et al. (2012). The text-based CAPTCHA is used for Optical Character Recognition (OCR). OCR is strong enough to solve text-based CAPTCHA challenges. However, it still has challenges regarding its robustness in solving CAPTCHA problems Kaur and Behal (2015). These CAPTCHA challenges are extensive with ongoing modern technologies. Machines can solve them, but humans cannot. These automated, complex CAPTCHA-creating tools can be broken down using various OCR techniques. Some studies claim that they can break any CAPTCHA with high efficiency. The existing work also recommends strategies to increase the keyword size and another method of crossing lines from keywords that use only straight lines and a horizontal direction. It can break easily using different transformations, such as the Hough transformation. It is also suggested that single-character recognition is used from various angles, rotations, and views to make more robust and challenging CAPTCHAs. Bursztein et al. (2011).

The concept of reCAPTCHA was introduced in 2008. It was initially a rough estimation. It was later improved and was owned by Google to decrease the time taken to solve it. The un-solvable reCAPTCHA's were then considered to be a new challenge for OCRs Von Ahn et al. (2008). The usage of computer vision and image processing as a CAPTCHA solver or breaker was increased if segmentation was performed efficiently George et al. (2017), Ye et al. (2018). The main objective or purpose of making a CAPTCHA solver is to protect CAPTCHA breakers. By looking into CAPTCHA solvers, more challenging CAPTCHAs can be generated, and they may lead to a more secure web that is protected against malicious attacks Rai et al. (2021). A benchmark or suggestion for CAPTCHA creation was given by Chellapilla et al.: Humans should solve the given CAPTCHA challenge with a 90% success rate, while machines ideally solve only one in every 10,000 CAPTCHAs Chellapilla et al. (2005).

Modern AI yields CAPTCHAs that can solve problems in a few seconds. Therefore, creating CAPTCHAs that are easily interpretable for humans and unsolvable for machines is an open challenge. It is also observed that humans invest a substantial amount of time daily solving CAPTCHAs Von Ahn et al. (2008). Therefore, reducing the amount of time humans need to solve them is another challenge. Various considerations need to be made, including text familiarity, visual appearance, distortions, etc. Commonly in text-based CAPTCHAs, the well-recognized languages are used that have many dictionaries that make them easily breakable. Therefore, we may need to make unfamiliar text from common languages such as phonetic text is not ordinary language that is pronounceable Wang and Bentley (2006). Similarly, the color of the foreground and the background of CAPTCHA images is also an essential factor, as many people have low or normal eyesight or may not see them. Therefore, a visually appealing foreground and background with distinguishing colors are recommended when creating CAPTCHAs. Distortions from periodic or random manners, such as affine transformations, scaling, and the rotation of specific angles, are needed. These distortions are solvable for computers and humans. If the CAPTCHAs become unsolvable, then multiple attempts by a user are needed to read and solve them Yan and El Ahmad (2008).

In current times, Deep Convolutional neural networks (DCNN) are used in many medical Meraj et al. (2019), Manzoor et al. (2022), Mahum et al. (2021) and other real-life recognition applications Namasudra (2020) as well as insecurity threat solutions Lal et al. (2021). The security threats in IoT and many other aspects can also be controlled using blockchain methods Namasudra et al. (2021). Utilizing deep learning, the proposed study uses various image processing operations to normalize text-based image datasets. After normalizing the data, a single-word-caption-based OCR was designed with skipping connections. These skipping connections connect previous pictorial information to various outputs in simple Convolutional Neural Networks (CNNs), which possess visual information in the next layer only Ahn and Yim (2020).

The main contribution of this research work is as follows:

- A skipping-connection-based CNN framework is proposed that covers multiple aspects of features.
- We segment the characters from the given dataset images based on skipping-connection.

- 99 • A 5-fold validation scheme is used in a deep-learning-based network to remove bias, if any, which
- 100 leads to more promising results.
- 101 • The data are normalized using various image processing steps to make it more understandable for
- 102 the deep learning model.

103 LITERATURE REVIEW

104 Today in the growing and dominant field of AI, many real-life problems have been solved with the help
 105 of deep learning and other evolutionary optimized intelligent algorithms Rauf et al. (2021), Rauf et al.
 106 (2020). Various problems of different aspects using DL methods are solved, such as energy consumption
 107 analysis Gao et al. (2020b), time scheduling of resources to avoid time and resources wastage Gao et al.
 108 (2020c). Similarly, in cybersecurity, a CAPTCHA solver has provided many automated AI solutions,
 109 except OCR. Multiple proposed CNN models have used various types of CAPTCHA datasets to solve
 110 CAPTCHAs. The collected datasets have been divided into three categories: selection-, slide-, and
 111 click-based. Ten famous CAPTCHAs were collected from google.com, tencent.com, etc. The breaking
 112 rate of these CAPTCHAs was compared. CAPTCHA design flaws that may help to break CAPTCHAs
 113 easily were also investigated. The underground market used to solve CAPTCHAs was also investigated,
 114 and findings concerning scale, the commercial sizing of keywords, and their impact on CAPTCHAs were
 115 reported Weng et al. (2019). A proposed sparsity-integrated CNN used constraints to deactivate the fully
 116 connected connections in CNN. It ultimately increased the accuracy results compared to transfer learning,
 117 and simple CNN solutions Ferreira et al. (2019).

118 Image processing operations regarding erosion, binarization, and smoothing filters were performed
 119 for data normalization, where adhesion-character-based features were introduced and fed to a neural
 120 network for character recognition Hua and Guoqin (2017). The backpropagation method was claimed
 121 as a better approach for image-based CAPTCHA recognition. It has also been said that CAPTCHA
 122 has become the normal, secure authentication method in the majority of websites and that image-based
 123 CAPTCHAs are more valuable than text-based CAPTCHAs Saroha and Gill (2021). Template-based
 124 matching is performed to solve text-based CAPTCHAs, and preprocessing is also performed using
 125 Hough transformation and skeletonization. Features based on edge points are also extracted, and the
 126 points of reference with the most potential are taken. It is also claimed that the extracted features are
 127 invariant to position, language, and shapes. Therefore, it can be used for any merged, rotated, and other
 128 variation-based CAPTCHAs WANG (2017).

129 PayPal CAPTCHAs have been solved using correlation, and Principal Component Analysis (PCA)
 130 approaches. The primary steps of these studies include preprocessing, segmentation, and the recognition
 131 of characters. A success rate of 90% was reported using correlation analysis of PCA and using PCA
 132 only increased the efficiency to 97% Rathoura and Bhatiab (2018). A Faster Recurrent Neural Network
 133 (F-RNN) has been proposed to detect CAPTCHAs. It was suggested that the depth of a network could
 134 increase the mean average precision value of CAPTCHA solvers, and experimental results showed that
 135 feature maps of a network could be obtained from convolutional layers Du et al. (2017). Data creation
 136 and cracking have also been used in some studies. For visually impaired people, there should be solutions
 137 to CAPTCHAs. A CNN network named CAPTCHANet has been proposed.

138 A 10-layer network was designed and was improved later with training strategies. A new CAPTCHA
 139 using Chinese characters was also created, and it removed the imbalance issue of class for model training.
 140 A statistical evaluation led to a higher success rate Zhang et al. (2021). A data selection approach
 141 automatically selected data for training purposes. The data augmenter later created four types of noise
 142 to make CAPTCHAs difficult for machines to break. However, the reported results showed that, in
 143 combination with the proposed preprocessing method, the results were improved to 5.69% Che et al.
 144 (2021). Some recent studies on CAPTCHA recognition are shown in Table 1.

145 The pre-trained model of object recognition has an excellent structural CNN. A similar study used
 146 a well-known VGG network and improved the structure using focal loss Wang and Shi (2021). The
 147 image processing operations generated complex data in text-based CAPTCHAs, but there may be a high
 148 risk of breaking CAPTCHAs using common languages. One study used the Python Pillow library to
 149 create Bengali-, Tamil-, and Hindi-language-based CAPTCHAs. These language-based CAPTCHAs were
 150 solved using D-CNN, which proved that the model was also confined by these three languages Ahmed
 151 and Anand (2021). A new, automatic CAPTCHA creating and solving technique using a simple 15-layer

Table 1. Recent CAPTCHA recognition-based studies and their details.

Reference	Year	Dataset	Method	Results
Wang and Shi (2021)	2021	CNKI CAPTCHA, Random Generated, Zhengfang CAPTCHA	Binarization, smoothing, segmentation and annotation with Adhesion and more interference	Recognition rate= 99%, 98.5%, 97.84%
Ahmed and Anand (2021)	2021	Tamil, Hindi and Bengali	Pillow Library, CNN	~
Bostik et al. (2021)	2021	Private created Dataset	15-layer CNN	Classification accuracy= 80%
Kumar and Singh (2021)	2021	Private	7-Layer CNN	Classification Accuracy= 99.7%
Dankwa and Yang (2021)	2021	4-words Kaggle Dataset	CNN	Classification Accuracy=100%
Wang et al. (2021b)	2021	Private GAN based dataset	CNN	Classification Accuracy= 96%, overall = 74%
Thobhani et al. (2020)	2020	Weibo, Gregwar	CNN	Testing Accuracy= 92.68% Testing Accuracy= 54.20%

152 CNN was proposed to remove the manual annotation problem.

153 Various fine-tuning techniques have been used to break 5-digit CAPTCHAs and have achieved 80%
 154 classification accuracies Bostik et al. (2021). A privately collected dataset was used in a CNN approach
 155 with 7 layers that utilize correlated features of text-based CAPTCHAs. It achieved a 99.7% accuracy
 156 using its image database, and CNN architecture Kumar and Singh (2021). Another similar approach was
 157 based on handwritten digit recognition. The introduction of a CNN was initially discussed, and a CNN
 158 was proposed for twisted and noise-added CAPTCHA images Cao (2021). A deep, separable CNN for
 159 four-word CAPTCHA recognition achieved 100% accurate results with the fine-tuning of a separable
 160 CNN concerning their depth. A fine-tuned, pre-trained model architecture was used with the proposed
 161 architecture and significantly reduced the training parameters with increased efficiency Dankwa and Yang
 162 (2021).

163 A visual-reasoning CAPTCHA (known as a Visual Turing Test (VTT)) has been used in security
 164 authentication methods, and it was easy to break using holistic and modular attacks. One study focused
 165 on a visual-reasoning CAPTCHA and showed an accuracy of 67.3% against holistic CAPTCHAs and
 166 an accuracy of 88% against VTT CAPTCHAs. Future directions were to design VTT CAPTCHAs to
 167 protect against these malicious attacks Gao et al. (2021). To provide a more secure system in text-based
 168 CAPTCHAs, a CAPTCHA defense algorithm was proposed. It used a multi-character CAPTCHA
 169 generator using an adversarial perturbation method. The reported results showed that complex CAPTCHA
 170 generation reduces the accuracy of CAPTCHA breaker up to 0.06% Wang et al. (2021a). The Generative
 171 Adversarial Network (GAN) based simplification of CAPTCHA images adopted before segmentation
 172 and classification. A CAPTCHA solver is presented that achieves 96% success rate character recognition.
 173 All other CAPTCHA schemes were evaluated and showed a 74% recognition rate. These suggestions
 174 for CAPTCHA designers may lead to improved CAPTCHA generation Wang et al. (2021b). A binary

image-based CAPTCHA recognition framework is proposed to generate a certain number of image copies from a given CAPTCHA image to train a CNN model. The The Weibo dataset showed that the 4-character recognition accuracy on the testing set was 92.68%, and the Gregwar dataset achieved a 54.20% accuracy on the testing set Thobhani et al. (2020).

The studies discussed above yield information about text-based CAPTCHAs as well as other types of CAPTCHAs. Most studies used DL methods to break CAPTCHAs, and time and unsolvable CAPTCHAs are still an open challenge. More efficient DL methods need to be used that, though they may not cover other datasets, should be robust to them. The locally developed datasets are used by many of the studies make the proposed studies less robust. However, publicly available datasets could be used so that they could provide more robust and confident solutions.

METHODOLOGY

Recent studies based on deep learning have shown excellent results to solve a CAPTCHA. However, simple CNN approaches may detect lossy pooled incoming features when passing between convolution and other pooling layers. Therefore, the proposed study utilizes skip connection. To remove further bias, a 5-fold validation approach is adopted. The proposed study presents a CAPTCHA solver framework using various steps, as shown in Figure. 1. The data are normalized using various image processing steps to make it more understandable for the deep learning model. This normalized data is segmented per character to make an OCR-type deep learning model that can detect each character from each aspect. At last, the 5-fold validation method is reported and yields promising results.




Figure 1. The Proposed Framework for CAPTCHA Recognition.

The two datasets used for CAPTCHA recognition have 4 and 5 words in them. The 5-word dataset has a horizontal line in it with overlapping text. Segmenting and recognizing such text is challenging due to its un-clearance. The other dataset of 4 characters was not as challenging to segment, as no line intersected them, and character rotation scaling needs to be considered. Their preprocessing and segmentation are explained in the next section. The dataset is explored in detail before and after preprocessing and segmentation.

Datasets

There are two public datasets available on Kaggle that are used in the proposed study. There are 5 and 4 characters in both datasets. There are different numbers of numeric and alphabetic characters in them. There are 1040 images in the five-character dataset (d_1) and 9955 images in the 4-character dataset (d_2).

204 There are 19 types of characters in the d_1 dataset, and there are 32 types of characters in the d_2 dataset.
 205 Their respective dimensions and extension details before and after segmentation are shown in Table 2.
 206 The frequencies of each character in both datasets are shown in Figure 2.




Figure 2. Character-wise Frequencies (Row-1: 4-Character Dataset 1 (d_2); Row-2: five-character Dataset 2 (d_1)).

207 The frequency of each character varies in both datasets, and the number of characters also varies. In
 208 the d_2 dataset, although there is no complex inner line intersection and a merging of texts is found, more
 209 characters and their frequencies are. However, the d_1 dataset has complex data and a low number of
 210 characters and frequencies, as compared to d_2 . Initially, d_1 has the dimensions 50 x 200 x 3, where 50
 211 represents the rows, 200 represents the columns, and 3 represents the color depth of the given images. d_2
 212 has image dimensions of 24 x 72 x 3, where 24 is the rows, 72 is the columns, and 3 is the color depth of
 213 given images. These datasets have almost the same character location. Therefore, they can be manually
 214 cropped to train the model on each character in an isolated form. However, their dimensions may vary for
 215 each character, which may need to be equally resized. The input images of both datasets were in Portable
 216 Graphic Format (PNG) and did not need to change. After segmenting both dataset images, each character
 217 is resized to 20 x 24 in both datasets. This size covers each aspect of the visual binary patterns of each
 218 character. The dataset details before and after resizing are shown in Table 2.

219 The summarized details of the used datasets in the proposed study are shown in Table 2. The
 220 dimensions of the resized image per character mean that, when we segment the characters from the
 221 given dataset images, their sizes vary from dataset to dataset and from character type to character type.
 222 Therefore, the optimal size at which the image data for each character is not lost is 20 rows by 24 columns,
 223 which is set for each character.

224 Preprocessing and Segmentation

225 d_1 dataset images do not need any complex image processing to segment them into a normalized form.
 226 d_2 needs this operation to remove the central intersecting line of each character. This dataset can be
 227 normalized to isolate each character correctly. Therefore, three steps are performed on the d_1 dataset.
 228 It is firstly converted to greyscale; it is then converted to a binary form, and their complement is lastly
 229 taken. In the d_2 dataset, 2 additional steps of erosion and area-wise selection are performed to remove

Table 2. Description of the employed dataset.

Properties	d1	d2
Image dimension	50x200x3	24x72x3
Extension	PNG	PNG
Number of Images	9955	1040
Character Types	32	19
Resized Image Dimension (Per Character)	20x24x1	20x24x1

the intersection line and the edges of characters. The primary steps of both datasets and each character isolation are shown in Figure 3.




Figure 3. Preprocessing and Isolation of characters in both datasets (Row-1: the d1 dataset, binarization, erosion, area-wise selection, and segmentation; Row-2: binarization and isolation of each character).

Binarization is the most needed step in order to understand the structural morphology of a certain character in a given image. Therefore, grayscale conversion of images is performed to perform binarization, and images are converted from greyscale to a binary format. The RGB format image has 3 channels in them: Red, Green, and Blue. Let Image $I_{(x,y)}$ be the input RGB image, as shown in Eq. 1. To convert these input images into grayscale, Eq. 2 is performed.

$$\text{Input Image} = I_{(x,y)} \quad (1)$$

In Eq. 1, I is the given image, and x and y represent the rows and columns. The grayscale conversion is performed using Eq. 2:

$$\text{Grey}(x,y) \leftarrow \sum_{i=n}^j (0.2989 * R, 0.5870 * G, 0.1140 * B) \quad (2)$$

In Eq. 2, i is the iterating row position, j is the interacting column position of the operating pixel at a certain time, and R , G , and B are the red, green, and blue pixel values of that pixel. The multiplying constant values convert to all three values of the respective channels to a new grey-level value in the range

242 of 0–255. $Grey(x, y)$ is the output grey-level of a given pixel at a certain iteration. After converting to grey-
 243 level, the binarization operation is performed using Bradly's method, which calculates a neighborhood
 244 base threshold to convert into 1 and 0 values to a given grey-level matrix of dimension 2. The neighborhood
 245 threshold operation is performed using Eq. 3.

$$B(x, y) \leftarrow 2 * \lfloor \text{size}(\frac{Grey(x, y)}{16} + 1) \rfloor \quad (3)$$

246 In Eq. 3, the output $B(x, y)$ is the neighborhood-based threshold that is calculated as the $1/8^{th}$
 247 neighborhood of a given $Grey(x, y)$ image. However, the floor is used to obtain a lower value to avoid
 248 any miscalculated threshold value. This calculated threshold is also called the adaptive threshold method.
 249 The neighborhood value can be changed to increase or decrease the binarization of a given image. After
 250 obtaining a binary image, the complement is necessary to highlight the object in a given image, taken as a
 251 simple inverse operation, calculated as shown in Eq. 4.

$$C(x, y) \leftarrow \frac{1}{B(x, y)} \quad (4)$$

252 In Eq. 4, the available 0 and values are inverted to their respective values of each pixel position x and
 253 y . The inverted image is used as an isolation process in the case of the d_2 dataset. In the case of the d_1 ,
 254 further erosion is needed. Erosion is an operation that uses a structuring element concerning its shape. The
 255 respective shape is used to remove pixels from a given binary image. In the case of a CAPTCHA image,
 256 the intersected line is removed using a line-type structuring element. The line-type structuring element
 257 uses a neighborhood operation. In the proposed study case, a line of size 5 with an angle dimension of 90
 258 is used, and the intersecting line for each character in the binary image is removed, as we can see in Figure
 259 3, row 1. The erosion operation with respect to a 5 length and a 90 angle is calculated as shown in Eq. 5.

$$C \ominus L \leftarrow x \in E | B_x \subseteq C \quad (5)$$

260 In Eq. 5, C is the binary image, L is the line type structuring element of line type, and x is the resultant
 261 eroded matrix of the input binary image C . B_x is the subset of a given image, as it is extracted from a given
 262 image C . After erosion, there is noise in some images that may lead to the wrong interpretation of that
 263 character. Therefore, to remove noise, the neighborhood operation is again utilized, and 8 neighborhood
 264 operations are used to a given threshold of 20 pixels for 1 value, as the noise value remains lower than the
 265 character in that binary image. To calculate it, an area calculation using each pixel is necessary. Therefore,
 266 by iterating an 8 by 8 neighborhood operation, 20 pixels consisting of the area are checked to remove
 267 those areas, and other more significant areas remain in the output image. The sum of a certain area with a
 268 maximum of 1 is calculated as shown in Eq. 6.

$$S(x, y) \leftarrow \sum_{i=1}^j \max(B_x |xi - xj|, B_x |yi - yj|) \quad (6)$$

269 In Eq. 6, the given rows (i) and columns (j) of a specific eroded image B_x are used to calculate the
 270 resultant matrix by extracting each pixel value to obtain one's value from the binary image. The max will
 271 return only values that will be summed to obtain an area that will be compared with threshold value T .
 272 The noise will then be removed, and final isolation is performed to separate each normalized character.

273 CNN Training for Text Recognition

$$convo(I, W)_{x, y} = \sum_{a=1}^{N_C} \sum_{b=1}^{N_R} W_{a, b} * I_{x+a-1, y+b-1} \quad (7)$$

274 In the above equation, we formulate a convolutional operation for a 2D image that represents $I_{x, y}$,
 275 where x and y are the rows and columns of the image, respectively. $W_{x, y}$ represents the convolving window
 276 concerning rows and columns x and y . The window will iteratively be multiplied with the respective
 277 element of the given image and then return the resultant image in $convo(I, W)_{x, y}$. N_C and N_R are the
 278 numbers of rows and columns starting from 1, a represents columns, and b represents rows.

Batch Normalization Layer

Its basic formula is to calculate a single component value, which can be represented as

$$Bat' = \frac{a - M[a]}{\sqrt{var(a)}} \quad (8)$$

The calculated new value is represented as Bat' , a is any given input value, and $M[a]$ is the mean of that given value, where in the denominator the variance of input a is represented as $var(a)$. The further value is improved layer by layer to give a finalized normal value with the help of alpha gammas, as shown below:

$$Bat'' = \gamma * Bat' + \beta \quad (9)$$

The extended batch normalization formulation improved in each layer with the previous Bat' value.

ReLU

ReLU excludes the input values that are negative and retains positive values. Its equation can be written as

$$ReLU = \begin{cases} x = x & \text{if } x > 0 \\ x = 0 & \text{if } x \leq 0 \end{cases} \quad (10)$$

where x is the input value and directly outputs the value if it is greater than zero; if values are less than 0, negative values are replaced with 0.

Skip-Connection

The Skip connection is basically concatenating the previous sort of pictorial information to the next convolved feature maps of network. In proposed network, the ReLU-1 information is saved and then after 2nd and 3rd ReLU layer, these saved information is concatenated with the help of an addition layer. In this way, the skip-connection is added that makes it different as compared to conventional deep learning approaches to classify the guava disease. Moreover, the visualization of these added feature information is shown in Figure 1.

Average Pooling

The average pooling layer is superficial as we convolve to the input from the previous layer or node. The coming input is fitted using a window of size $m \times n$, where m represents the rows, and n represents the column. The movement in the horizontal and vertical directions continues using stride parameters.

Many deep learning-based algorithms introduced previously, as we can see in Table 1, ultimately use CNN-based methods. However, all traditional CNN approaches using convolve blocks and transfer learning approaches may take important information when they pool down to incoming feature maps from previous layers. Similarly, the testing and validation using conventional training, validation, and testing may be biased due to less data testing than the training data. Therefore, the proposed study uses a 1-skip connection while maintaining other convolve blocks; inspired by the K-Fold validation method, it splits up both datasets' data into five respective folds. The dataset, after splitting into five folds, is trained and tested in a sequence. However, these five-fold results are taken as a means to report final accuracy results. The proposed CNN contains 16 layers in total, and it includes three major blocks containing convolutional, batch normalization, and ReLU layers. After these nine layers, an additional layer adds incoming connections, a skip connection, and 3rd-ReLU-layer inputs from the three respective blocks. Average pooling, fully connected, and softmax layers are added after skipping connections. All layer parameters and details are shown in Table 3.

In Table 3, all learnable weights of each layer are shown. For both datasets, output categories of characters are different. Therefore, in the dense layer of the five-fold CNN models, the output class was 19 for five models, and the output class was 32 categories in the other five models. The skip connection has more weights than other convolution layers. Each model is compared regarding its weight learning and is shown in Figure 4.

The figure shows convolve 1, batch normalization, and skip connection weights. The internal layers have a more significant number of weights or learnable parameters, and the different or contributing

Table 3. Parameters setting and learnable weights for proposed framework

Number	Layers Name	Category	Parameters	Weights/Offset	Padding	Stride
1	Input	Image Input	24 x 20 x 1	-	-	-
2	Conv (1)	Convolution	24 x 20 x 8	3x3x1x8	Same	1
3	BN (1)	Batch Normalization	24 x 20 x 8	1x1x8	-	-
4	ReLU (1)	ReLU	24 x 20 x 8	-	-	-
5	Conv (2)	Convolution	12 x 10 x 16	3x3x8x16	Same	2
6	BN (2)	Batch Normalization	12 x 10 x 16	1x1x16	-	-
7	ReLU (2)	ReLU	12 x 10 x 16	-	-	-
8	Conv (3)	Convolution	12 x 10 x 32	3x3x16x32	Same	1
9	BN (3)	Batch Normalization	12 x 10 x 32	1x1x32	-	-
10	ReLU (3)	ReLU	12 x 10 x 32	-	-	-
11	Skip-connection	Convolution	12 x 10 x 32	1x1x8x32	2	0
12	Add	Addition	12 x 10 x 32	-	-	-
13	Pool	Average Pooling	6 x 5 x 32	-	2	0
14	FC	Fully connected	1 x 1 x 19 (d2)	19 x 960 (d2)	-	-
			1 x 1 x 32 (d1)	32 x 960 (d1)		
15	Softmax	Softmax	1 x 1 x 19	-	-	-
16	Class Output	Classification	-	-	-	-

connection weights are shown in Figure 4. Multiple types of feature maps are included in the figure. However, the weights of one dataset are shown. In the other dataset, these weights may vary slightly. The skip-connection weights have multiple features that are not in a simple convolve layer. Therefore, we can say that the proposed CNN architecture is a new way to learn multiple types of features compared to previous studies that use a traditional CNN. This connection may be used in other aspects of text and object recognition and classification.

Later on, by obtaining these significant, multiple features, the proposed study utilizes the K-fold validation technique by splitting the data into five splits. These multiple splits remove bias in the training and testing data and take the testing results as the mean of all models. In this way, no data will remain for training, and no data will be untested. The results ultimately become more confident than previous conventional approaches of CNN. The d_2 dataset has a clear, structured element in its segmented images; in d_1 , the isolated text images were not much clearer. Therefore, the classification results remain lower in this case, whereas in the d_2 dataset, the classification results remain high and usable as a CAPTCHA solver. The results of each character and dataset for each fold are discussed in the next section.




Figure 4. Five-fold weights with respective layers shown for multiple proposed CNN architectures.

RESULTS AND DISCUSSION

As discussed earlier, there are two datasets in the proposed framework. Both have a different number of categories and a different number of images. Therefore, separate evaluations of both are discussed and described in this section. Firstly, the five-character dataset is used by the 5-CNN models of same architecture, with a different split in the data. Secondly, the four-character dataset is used by the same architecture of the model, with a different output of classes.

Five-character Dataset (d_1)

The five-character dataset has 1040 images in it. After segmenting each type of character, it has 5200 total images. The data are then split into five folds: 931, 941, 925, 937, and 924. The remaining data difference is adjusted into the training set, and splitting was adjusted during the random selection of 20-20% of the total data. The training on four-fold data and the testing on the one-fold data are shown in Table 4.

In Table 4, there are 19 types of characters that have their fold-by-fold varying accuracy. The mean of all folds is given. The overall or mean of each fold and the mean of all folds are given in the last row. We can see that the Y character has a significant or the highest accuracy rate (95.40%) of validation compared to other characters. This may be due to its almost entirely different structure from other characters. The other highest accuracy is of the G character with 95.06%, which is almost equal to the highest with a slight difference. However, these two characters have a more than 95% recognition accuracy, and no other character is nearer to 95. The other characters have a range of accuracies from 81 to 90%. The least accurate M character is 62.08, and it varies in five folds from 53 to 74%. Therefore, we can say that M matches with other characters, and for this character recognition, we may need to concentrate on structural polishing for M input characters. To prevent CAPTCHA from breaking further complex designs among machines and making it easy for humans to do so, the other characters that achieve higher results need a high angle and structural change to not break with any machine learning model. This complex structure may be improved from other fine-tuning of a CNN, increasing or decreasing the skipping connection. The accuracy value can also improve. The other four-character dataset is more important because it has 32 types of characters and more images. This five-character dataset's lower accuracy may also be due to little data and less training. The other character recognition studies have higher accuracy rates on similar datasets, but they might be less confident than the proposed study due to an unbiased validation method. The four-character dataset recognition results are discussed in the next section.

Table 4. Five-character Dataset Accuracy (%) with five-fold text recognition testing on the CNN.

Character	Fold 1	Fold 2	Fold 3	Fold 4	Fold 5	Overall
2	87.23	83.33	89.63	83.33	78.72	84.48
3	87.76	75.51	87.75	85.71	93.87	86.12
4	84.31	88.46	90.196	90.19	92.15	89.06
5	84.31	80.39	90.00	94.11	84.00	86.56
6	86.95	76.59	82.61	91.304	80.43	87.58
7	89.36	87.23	86.95	85.10	84.78	86.68
8	89.58	79.16	91.66	89.58	87.50	87.49
B	81.81	73.33	97.72	82.22	90.09	85.03
C	87.23	79.16	85.10	80.85	80.85	82.64
D	91.30	78.26	91.30	86.95	95.55	88.67
E	62.79	79.54	79.07	93.18	79.07	78.73
F	92.00	84.00	93.87	94.00	81.63	89.1
G	95.83	91.83	100	93.87	93.75	95.06
M	64.00	56.00	53.061	74.00	67.34	62.08
N	81.40	79.07	87.59	76.74	82.35	81.43
P	97.78	78.26	82.22	95.65	97.78	90.34
W	95.24	83.72	90.47	100	83.33	90.55
X	89.58	87.50	82.97	85.41	82.98	85.68
Y	93.02	95.45	97.67	95.53	95.35	95.40
Overall	86.14	80.77	87.24	87.73	85.71	85.52

Four-Character Dataset (d_2)

The four-character dataset has a higher frequency of each character compared to the five-character dataset, and the number of characters is also higher. The same five-fold splits were performed on this dataset characters as well. After applying the five folds, the number of characters in each fold was 7607, 7624, 7602, 7617, and 7595, respectively, and the remaining images from the 38,045 images of individual characters were adjusted into the training sets of each fold. The results of each character w.r.t each fold and the overall mean are given in Table 5.

From Table 5, it can be observed that almost every character was recognized with 99% accuracy. The highest accuracy of character D was 99.92 and remained 100% in the four-folds. Only one fold showed a 99.57% accuracy. From this point, we can state that the proposed study removed bias, if there was any, from the dataset by doing splits. Therefore, it is necessary to make folds in a deep learning network. Most studies use a 1-fold approach only. The 1-fold approach is at a high risk. It is also important that the character m achieved the lowest accuracy in the case of the five-character CAPTCHA. In this four-character CAPTCHA, 98.58% was accurately recognized. Therefore, we can say that the structural morphology of M in the five-character CAPTCHA better avoids any CAPTCHA solver method. The highest results show that this four-character CAPTCHA is at a high risk, and line intersection, word joining, and correlation may break prevent the CAPTCHA from breaking. Many approaches before have been proposed to recognize the CAPTCHA, and most of them have used a conventional structure. The proposed study has used a more confident validation approach with multi-aspect feature extraction. Therefore, it can be used as a more promising approach to break CAPTCHA images and to test the CAPTCHA design made by CAPTCHA designers. In this way, CAPTCHA designs can be protected against new approaches to deep learning. The graphical illustration of validation accuracy and the losses for both datasets on all folds is shown in Figure 5.




Figure 5. The validation loss and validation accuracy graphs are shown for each fold of the CNN (Row-1: five-character CAPTCHA; Row-2: four-character CAPTCHA).

The five- and four-character CAPTCHA fold validation losses and accuracies are shown. It can be observed that the all folds of the five-character CAPTCHA reached close to 90%, and only the 2nd fold value remained at 80.77%. It is also important to state that, in this fold, there were cases that may not be covered in other deep learning approaches, and their results remain at risk. Similarly, a four-character CAPTCHA with a greater number of samples and less complex characters should not be used, as it can break easily compared to the five-character CAPTCHA. CAPTCHA-recognition-based studies have used self-generated or augmented datasets to propose CAPTCHA solvers. Therefore, the number of images, their spatial resolution sizes and styles, and other results have become incomparable. The proposed study mainly focuses on a better validation technique using deep learning with multi-aspect feature via skipping connections in a CNN. With some character-matching studies, we performed a comparison to make the proposed study more reliable.

Table 5. Four-character dataset Accuracy (%) with five-fold text recognition testing on the CNN.

Character	Fold 1	Fold 2	Fold 3	Fold 4	Fold 5	Overall
2	97.84	99.14	99.57	99.14	98.27	98.79
3	97.02	94.92	98.72	95.75	96.17	96.52
4	97.87	97.46	99.15	98.72	99.57	98.55
5	98.76	98.76	99.17	100	98.35	99.01
6	100	95.65	99.56	99.13	99.13	98.69
7	98.80	99.60	99.19	100	99.20	99.36
8	99.15	98.72	97.42	97.86	98.28	98.29
9	98.85	96.55	98.08	98.46	100	98.39
A	97.85	98.71	99.13	98.71	98.28	98.54
B	99.57	96.59	98.72	98.72	96.15	97.95
C	99.58	98.75	99.16	99.58	99.17	99.25
D	100	100	100	99.57	100	99.92
E	99.18	97.57	100	99.59	98.37	98.94
F	98.69	98.26	100	97.82	97.83	98.52
G	98.76	97.93	100	96.69	98.75	98.43
H	99.58	97.90	100	99.58	99.58	99.33
J	100	98.72	99.57	100	100	99.66
K	99.15	99.58	100	99.16	100	99.58
L	97.41	98.28	100	99.14	99.14	98.79
M	99.16	96.23	99.16	100	98.33	98.58
N	99.58	97.10	99.17	99.58	98.76	98.83
P	98.35	97.94	98.77	97.94	96.28	97.86
Q	100	100	99.58	99.58	99.57	99.75
R	99.58	99.17	99.17	99.59	97.50	99.00
S	98.75	99.58	100	100	98.74	99.42
T	97.47	97.90	98.73	97.47	98.31	97.98
U	100	97.43	99.57	98.28	98.71	98.80
V	100	98.67	98.67	98.67	98.22	98.47
W	100	100	100	99.17	99.17	99.67
X	99.15	97.46	100	99.15	100	99.15
Y	97.90	98.33	98.74	98.74	99.58	98.66
Z	99.17	98.75	99.16	99.58	99.16	99.16
Overall	98.97	98.18	99.32	98.92	98.71	98.82

Table 6. Four-character dataset with five-fold text recognition testing on a CNN.

References	No. of Characters	Method	Results
Du et al. (2017)	6	Faster R-CNN	Accuracy= 98.5%
	4		Accuracy=97.8%
	5		Accuracy=97.5%
Chen et al. (2019)	4	Selective D-CNN	Success rate= 95.4%
Bostik et al. (2021)	Different	CNN	Accuracy= 80%
Bostik and Klecka (2018)	Different	KNN	Precision=98.99%
		SVN	99.80%
		Feed forward-Net	98.79%
Proposed Study	4	Skip-CNN with 5-Fold Validation	Accuracy= 98.82%
	5	-	Accuracy=85.52%

In Table 6, we can see that various studies have used different numbers of characters with self-collected and generated datasets, and comparisons have been made. Some studies have considered the number of dataset characters. Accuracy is not comparable, as it uses the five-fold validation method, and the others only used 1-fold. Therefore, the proposed study outperforms in each aspect, in terms of the proposed CNN framework and its validation scheme.

CONCLUSION

The proposed study uses a different approach to deep learning to solve CAPTCHA problems. It proposed a skip-CNN connection network to break text-based CAPTCHA's. Two CAPTCHA datasets are discussed and evaluated character by character. The proposed study is confident to report results, as it removed biases (if any) in datasets using a five-fold validation method. The results are also improved as compared to previous studies. The reported higher results claim that these CAPTCHA designs are at high risk, as any malicious attack can break them on the web. Therefore, the proposed CNN could test CAPTCHA designs to solve them more confidently in real-time. Furthermore, the proposed study has used the publicly available datasets to perform training and testing on them, making it a more robust approach to solve text-based CAPTCHA's.

Many studies have used deep learning to break CAPTCHAs, as they have focused on the need to design CAPTCHAs that do not consume user time and resist CAPTCHA solvers. It would make our web systems more secure against malicious attacks. However, In the future, the data augmentation methods and more robust data creation methods can be applied on CAPTCHA datasets where intersecting line-based CAPTCHA's are more challenging to break that can be used. Similarly, the other local languages based CAPTCHA's also can be solved using similar DL models.

REFERENCES

- Ahmed, S. S. and Anand, K. M. (2021). Convolution neural network-based captcha recognition for indic languages. In *Data Engineering and Intelligent Computing*, pages 493–502. Springer.
- Ahn, H. and Yim, C. (2020). Convolutional neural networks using skip connections with layer groups for super-resolution image reconstruction based on deep learning. *Applied Sciences*, 10(6):1959.
- Azad, S. and Jain, K. (2013). Captcha: Attacks and weaknesses against ocr technology. *Global Journal of Computer Science and Technology*.
- Baird, H. S. and Popat, K. (2002). Human interactive proofs and document image analysis. In *International Workshop on Document Analysis Systems*, pages 507–518. Springer.
- Bostik, O., Horak, K., Kratochvila, L., Zemcik, T., and Bilik, S. (2021). Semi-supervised deep learning approach to break common captchas. *Neural Computing and Applications*, pages 1–11.

- 430 Bostik, O. and Klecka, J. (2018). Recognition of captcha characters by supervised machine learning
431 algorithms. *IFAC-PapersOnLine*, 51(6):208–213.
- 432 Bursztein, E., Martin, M., and Mitchell, J. (2011). Text-based captcha strengths and weaknesses. In
433 *Proceedings of the 18th ACM conference on Computer and communications security*, pages 125–138.
- 434 Bursztein, E., Moscicki, A., Fabry, C., Bethard, S., Mitchell, J. C., and Jurafsky, D. (2014). Easy does it:
435 More usable captchas. In *Proceedings of the SIGCHI Conference on Human Factors in Computing*
436 *Systems*, pages 2637–2646.
- 437 Cao, Y. (2021). Digital character captcha recognition using convolution network. In *2021 2nd International*
438 *Conference on Computing and Data Science (CDS)*, pages 130–135. IEEE.
- 439 Che, A., Liu, Y., Xiao, H., Wang, H., Zhang, K., and Dai, H.-N. (2021). Augmented data selector to
440 initiate text-based captcha attack. *Security and Communication Networks*, 2021.
- 441 Chellapilla, K., Larson, K., Simard, P., and Czerwinski, M. (2005). Designing human friendly human
442 interaction proofs (hips). In *Proceedings of the SIGCHI conference on Human factors in computing*
443 *systems*, pages 711–720.
- 444 Chen, J., Luo, X., Liu, Y., Wang, J., and Ma, Y. (2019). Selective learning confusion class for text-based
445 captcha recognition. *IEEE Access*, 7:22246–22259.
- 446 Cruz-Perez, C., Starostenko, O., Uceda-Ponga, F., Alarcon-Aquino, V., and Reyes-Cabrera, L. (2012).
447 Breaking recaptchas with unpredictable collapse: Heuristic character segmentation and recognition. In
448 *Mexican Conference on Pattern Recognition*, pages 155–165. Springer.
- 449 Danchev, D. (2014). Google’s recaptcha under automatic fire from a newly launched recaptcha-
450 solving/breaking service, internet security threat updates & insights.
- 451 Dankwa, S. and Yang, L. (2021). An efficient and accurate depth-wise separable convolutional neural
452 network for cybersecurity vulnerability assessment based on captcha breaking. *Electronics*, 10(4):480.
- 453 Du, F.-L., Li, J.-X., Yang, Z., Chen, P., Wang, B., and Zhang, J. (2017). Captcha recognition based on
454 faster r-cnn. In *International Conference on Intelligent Computing*, pages 597–605. Springer.
- 455 Ferreira, D. D., Leira, L., Mihaylova, P., and Georgieva, P. (2019). Breaking text-based captcha with
456 sparse convolutional neural networks. In *Iberian conference on pattern recognition and image analysis*,
457 pages 404–415. Springer.
- 458 Gao, J., Wang, H., and Shen, H. (2020a). Machine learning based workload prediction in cloud computing.
459 In *2020 29th international conference on computer communications and networks (ICCCN)*, pages 1–9.
460 IEEE.
- 461 Gao, J., Wang, H., and Shen, H. (2020b). Smartly handling renewable energy instability in supporting a
462 cloud datacenter. In *2020 IEEE international parallel and distributed processing symposium (IPDPS)*,
463 pages 769–778. IEEE.
- 464 Gao, J., Wang, H., and Shen, H. (2020c). Task failure prediction in cloud data centers using deep learning.
465 *IEEE Transactions on Services Computing*.
- 466 Gao, Y., Gao, H., Luo, S., Zi, Y., Zhang, S., Mao, W., Wang, P., Shen, Y., and Yan, J. (2021). Research on
467 the security of visual reasoning {CAPTCHA}. In *30th {USENIX} Security Symposium ({USENIX}*
468 *Security 21)*.
- 469 George, D., Lehrach, W., Kansky, K., Lázaro-Gredilla, M., Laan, C., Marthi, B., Lou, X., Meng, Z., Liu,
470 Y., Wang, H., et al. (2017). A generative vision model that trains with high data efficiency and breaks
471 text-based captchas. *Science*, 358(6368).
- 472 Gheisari, M., Najafabadi, H. E., Alzubi, J. A., Gao, J., Wang, G., Abbasi, A. A., and Castiglione, A.
473 (2021). Obpp: An ontology-based framework for privacy-preserving in iot-based smart city. *Future*
474 *Generation Computer Systems*, 123:1–13.
- 475 Goswami, G., Powell, B. M., Vatsa, M., Singh, R., and Noore, A. (2014). Facedcaptcha: Face detection
476 based color image captcha. *Future Generation Computer Systems*, 31:59–68.
- 477 Hua, H. and Guoqin, C. (2017). A recognition method of captcha with adhesion character. *Int J Futur*
478 *Gener Commun Netw*, 10(8):59–70.
- 479 Kaur, K. and Behal, S. (2015). Designing a secure text-based captcha. *Procedia Computer Science*,
480 57:122–125.
- 481 Kumar, A. and Singh, A. P. (2021). Contour based deep learning engine to solve captcha. In *2021 7th*
482 *International Conference on Advanced Computing and Communication Systems (ICACCS)*, volume 1,
483 pages 723–727. IEEE.
- 484 Lal, S., Rehman, S. U., Shah, J. H., Meraj, T., Rauf, H. T., Damaševičius, R., Mohammed, M. A., and

- 485 Abdulkareem, K. H. (2021). Adversarial attack and defence through adversarial training and feature
486 fusion for diabetic retinopathy recognition. *Sensors*, 21(11):3922.
- 487 Madar, B., Kumar, G. K., and Ramakrishna, C. (2017). Captcha breaking using segmentation and
488 morphological operations. *International Journal of Computer Applications*, 166(4):34–38.
- 489 Mahum, R., Rehman, S. U., Meraj, T., Rauf, H. T., Irtaza, A., El-Sherbeeney, A. M., and El-Meligy, M. A.
490 (2021). A novel hybrid approach based on deep CNN features to detect knee osteoarthritis. *Sensors*,
491 21(18):6189.
- 492 Manzoor, K., Majeed, F., Siddique, A., Meraj, T., Rauf, H. T., El-Meligy, M. A., Sharaf, M., and Elgawad,
493 A. E. E. A. (2022). A lightweight approach for skin lesion detection through optimal features fusion.
494 *Computers, Materials & Continua*, 70(1):1617–1630.
- 495 Meraj, T., Hassan, A., Zahoor, S., Rauf, H. T., Lali, M. I., Ali, L., and Bukhari, S. A. C. (2019). Lungs
496 nodule detection using semantic segmentation and classification with optimal features.
- 497 Namasudra, S. (2020). Fast and secure data accessing by using dna computing for the cloud environment.
498 *IEEE Transactions on Services Computing*.
- 499 Namasudra, S., Deka, G. C., Johri, P., Hosseinpour, M., and Gandomi, A. H. (2021). The revolution
500 of blockchain: State-of-the-art and research challenges. *Archives of Computational Methods in*
501 *Engineering*, 28(3):1497–1515.
- 502 Obimbo, C., Halligan, A., and De Freitas, P. (2013). Captchall: an improvement on the modern text-based
503 captcha. *procedia computer science*, 20:496–501.
- 504 Priya, L. D. and Karthik, S. (2013). Secure captcha input based spam prevention. *IJESE*, 1(7).
- 505 Rai, N. et al. (2021). Captcha recognition using generative adversarial network implementation.
- 506 Rathoura, N. and Bhatiab, V. (2018). Recognition method of text captcha using correlation and principle
507 component analysis.
- 508 Rauf, H. T., Bangyal, W. H. K., and Lali, M. I. (2021). An adaptive hybrid differential evolution algorithm
509 for continuous optimization and classification problems. *Neural Computing and Applications*, pages
510 1–27.
- 511 Rauf, H. T., Malik, S., Shoaib, U., Irfan, M. N., and Lali, M. I. (2020). Adaptive inertia weight bat
512 algorithm with sugeno-function fuzzy search. *Applied Soft Computing*, 90:106159.
- 513 Roshanbin, N. and Miller, J. (2013). A survey and analysis of current captcha approaches. *Journal of*
514 *Web Engineering*, pages 001–040.
- 515 Saroha, R. and Gill, S. (2021). Strengthening pix captcha using trainlm function in backpropagation. In
516 *Rising Threats in Expert Applications and Solutions*, pages 679–686. Springer.
- 517 Sudarshan Soni, D. and Bonde, P. (2017). E-captcha: A two way graphical password based hard ai
518 problem. *International Journal on Recent and Innovation Trends in Computing and Communication*,
519 5(6):418–421.
- 520 Thobhani, A., Gao, M., Hawbani, A., Ali, S. T. M., and Abdussalam, A. (2020). Captcha recognition
521 using deep learning with attached binary images. *Electronics*, 9(9):1522.
- 522 Von Ahn, L., Blum, M., Hopper, N. J., and Langford, J. (2003). Captcha: Using hard ai problems for
523 security. In *International conference on the theory and applications of cryptographic techniques*, pages
524 294–311. Springer.
- 525 Von Ahn, L., Maurer, B., McMillen, C., Abraham, D., and Blum, M. (2008). recaptcha: Human-based
526 character recognition via web security measures. *Science*, 321(5895):1465–1468.
- 527 Wang, S., Zhao, G., and Liu, J. (2021a). Text captcha defense algorithm based on overall adversarial
528 perturbations. In *Journal of Physics: Conference Series*, volume 1744, page 042243. IOP Publishing.
- 529 Wang, S.-Y. and Bentley, J. L. (2006). Captcha challenge tradeoffs: Familiarity of strings versus
530 degradation of images. In *18th International Conference on Pattern Recognition (ICPR'06)*, volume 3,
531 pages 164–167. IEEE.
- 532 Wang, Y., Wei, Y., Zhang, M., Liu, Y., and Wang, B. (2021b). Make complex captchas simple: A fast text
533 captcha solver based on a small number of samples. *Information Sciences*.
- 534 Wang, Z. and Shi, P. (2021). Captcha recognition method based on cnn with focal loss. *Complexity*, 2021.
- 535 WANG, Z.-h. (2017). Recognition of text-based captcha with merged characters. *DEStech Transactions*
536 *on Computer Science and Engineering*, (cece).
- 537 Weng, H., Zhao, B., Ji, S., Chen, J., Wang, T., He, Q., and Beyah, R. (2019). Towards understanding the
538 security of modern image captchas and underground captcha-solving services. *Big Data Mining and*
539 *Analytics*, 2(2):118–144.

- 540 Xu, X., Liu, L., and Li, B. (2020). A survey of captcha technologies to distinguish between human and
541 computer. *Neurocomputing*, 408:292–307.
- 542 Yan, J. and El Ahmad, A. S. (2008). Usability of captchas or usability issues in captcha design. In
543 *Proceedings of the 4th symposium on Usable privacy and security*, pages 44–52.
- 544 Ye, G., Tang, Z., Fang, D., Zhu, Z., Feng, Y., Xu, P., Chen, X., and Wang, Z. (2018). Yet another text
545 captcha solver: A generative adversarial network based approach. In *Proceedings of the 2018 ACM*
546 *SIGSAC Conference on Computer and Communications Security*, pages 332–348.
- 547 Zhang, X., Liu, X., Sarkodie-Gyan, T., and Li, Z. (2021). Development of a character captcha recognition
548 system for the visually impaired community using deep learning. *Machine Vision and Applications*,
549 32(1):1–19.