

Evaluation of cultivated land quality using attention mechanism-back propagation neural network

Yulin Liu, Jiaolong Li, Chuang Liu and Jiangshu Wei

College of Information Engineering, Sichuan Agricultural University, Ya'an, Sichuan, China

ABSTRACT

Cultivated land quality is related to the quality and safety of agricultural products and to ecological safety. Therefore, reasonably evaluating the quality of land, which is helpful in identifying its benefits, is crucial. However, most studies have used traditional methods to estimate cultivated land quality, and there is little research on using deep learning for this purpose. Using Ya'an cultivated land as the research object, this study constructs an evaluation system for cultivated land quality based on seven aspects, including soil organic matter and soil texture. An attention mechanism (AM) is introduced into a back propagation (BP) neural network model. Therefore, an AM-BP neural network that is suitable for Ya'an cultivated land is designed. The sample is divided into training and test sets by a ratio of 7:3. We can output the evaluation results of cultivated land quality through experiments. Furthermore, they can be visualized through a pie chart. The experimental results indicate that the model effect of the AM-BP neural network is better than that of the BP neural network. That is, the mean square error is reduced by approximately 0.0019 and the determination coefficient is increased by approximately 0.005. In addition, this study obtains better results via the ensemble model. The quality of cultivated land in Yucheng District is generally good, i.e., mostly third and fourth grades. It conforms to the normal distribution. Lastly, the method has certain to evaluate cultivated land quality, providing a reference for future cultivated land quality evaluation.

Submitted 21 December 2021

Accepted 24 March 2022

Published 11 April 2022

Corresponding author

Jiangshu Wei,
weijiangshu66@163.com,
13486@sicau.edu.cn

Academic editor

Yilun Shang

Additional Information and
Declarations can be found on
page 14

DOI 10.7717/peerj-cs.948

© Copyright
2022 Liu et al.

Distributed under
Creative Commons CC-BY 4.0

OPEN ACCESS

Subjects Algorithms and Analysis of Algorithms, Artificial Intelligence, Data Mining and Machine Learning

Keywords Attention Mechanism, BP neural network, Cultivated land quality, Deep learning

INTRODUCTION

Cultivated land quality represents comprehensive properties of soil and lays the foundation for soil as a part of terrestrial ecology and crop production (*Smith et al., 2014*). Quality of arable land affects food production. Due to rapid socio-economic development and urbanization, the amount of cultivated land in China has been decreasing (*Lin et al., 2022*). In the case of Ya'an City, the situation is not optimistic. Its land carrying capacity faces increasing challenges as industrialisation and urbanisation have become the major themes of China's economic development (*Ding & Peng, 2018*). In addition, cultivated land, which is affected by various factors, including the use of new technologies and new varieties, face potential safety hazards, such as chemical and biological pollution, which damage long-term economic benefits and environmental protection (*Sun et al., 2018*). Therefore,

conducting farmland quality evaluation research is imperative to ensure food security and support new development.

In the evaluation of cultivated land quality, evaluation methods vary with different indicators selected under local conditions because cultivated land in different regions has distinct properties. With the updating of computer technology and mathematical knowledge, methods for farmland quality evaluation are developing rapidly (Liu, Zhang & Guo, 2010; Xie et al., 2018). Different methods may affect the evaluation result due to the selection of evaluation indicators, the division of indicator levels, or the weighted method (Viana et al., 2021). Therefore, formulating a reasonable cultivated land evaluation system that is conducive to conducting land development research is necessary. At present, common methods used to evaluate the quality of cultivated land include distance, number axis, factor, and sample plot methods (Tan et al., 2020). However, these methods cannot ensure the objectivity of evaluation because of the inclusion of subjective factors. Therefore, researchers are still exploring index systems for cultivated land quality. With the continued development of science and technology, deep learning algorithms, such as attention mechanism (Vaswani et al., 2017) (AM) and meta-learning (Finn, Abbeel & Levine, 2017), have emerged. Most of these algorithms are used in target detection and recognition. Some of these models have also been improved and applied to regression related to agriculture and agricultural produce, yielding good results (Nassar et al., 2020; Zhu et al., 2020; Gao et al., 2021). These algorithms can exhibit a combination of advantages by learning from one another and through various means of integration. In the era of information digitisation, information dominance constitutes a basic feature of the future; thus, studying how new methods can be combined with the evaluation of cultivated land quality is necessary (Liu et al., 2020b). Some scholars have achieved good results in their endeavour to integrate a back propagation (BP) neural network (Hao et al., 2021), a convolutional neural network (Liu et al., 2020a), a genetic algorithm (Liu et al., 2019), and the particle swarm optimisation algorithm (Wang et al., 2020) into the evaluation of cultivated land quality. However, the existing study of cultivated land quality is still lacking in combination with new deep learning algorithms.

A BP neural network is a multilayered feedforward neural network, which has strong nonlinear mapping ability and simple structure (Hu et al., 2021). It can build a model based on the existing data and use this model to solve regression or classification problems. Considering its extensive applications, a BP neural network constitutes the basis of the current study. AM is conducive to focusing attention on the key points in a neural network whilst disregarding unimportant factors (Pabón et al., 2022). Therefore, it can reduce the computational burden of processing high-dimensional input data and decrease data dimension through a structurally selected input subset.

The current study aims to find a more accurate evaluation method that is in line with reality and then develop it into a more standardised and scientific direction whilst providing a reference for other researchers. This work selects the cultivated land in the Yucheng District of Ya'an as the research object, devises a scientific system of cultivated land evaluation indicators, and evaluates the quality of cultivated land based on the AM-BP model, which can provide the attention score. In addition, an ensemble model based on

AM-BP is used to reduce errors. Based on the model results, a map is drawn to illustrate the condition of cultivated land quality in the Yucheng District of Ya'an City. This will help the local government to understand the status of cultivated land in this region, promoting the structural adjustment of agriculture. Moreover, it is conducive to the sustainable development.

MATERIALS AND METHODS

Overview of the research area

Located in the transition zone between the western edge of the Sichuan Basin and the Qinghai-Tibet Plateau, Yucheng District covers an area of 1067.3 km², and it belongs to one of the mountain counties around the basin. With the impact of urbanisation, the amount of arable land resources in China is decreasing (Deng *et al.*, 2015), with the per capita arable land area only 2/3 that of the world's average. Soil quality is seriously degraded whilst indiscriminate and excessive cultivation and occupation for construction occur ubiquitously. Therefore, the use of artificial intelligence methods for evaluating arable land is indispensable to understanding the current status of the quantity and quality of arable land resources in local areas. On the basis of this assessment, targeted arable land protection and management projects can be implemented to achieve smart and sustainable agricultural development.

Data source

The research data are derived from soil testing and fertilisation in Yucheng District, and they are provided by the Yucheng District Agricultural Bureau of Ya'an City. The average area of each sampling unit is 100–200 mu, setting up representative sampling points. The sampling depth is generally 0–20 cm, and the orchard can be collected in layers of 0 to 40 cm or 0–60 cm.

The accuracy rate is controlled by the use of standard samples. To identify the error, we add one standard sample for each batch. When the difference between the testing result and the standard value is out of the range of the standard deviation, the experimental procedure should be checked to find out the reason.

Data preprocessing

Data preprocessing is a significant task. Different dimensional units affect the results of our numerical analysis. Therefore, data must be standardised to ensure their comparability and eliminate such effects. The min-max standardisation for the data is as follows:

$$Z = \frac{x - x_{\min}}{x_{\max} - x_{\min}}, \quad (1)$$

where x_{\max} is the maximum value of the sample data, and x_{\min} is the minimum value of the sample data.

Construction of an index system

In accordance with the regional characteristics of cultivated land in the Yucheng District of Ya'an City, combined with data access, data statistics, expert consultation, and other

methods, indexes, such as surface soil texture, soil organic matter, soil nutrient elements, and pH value, are selected from natural elements to build a quality evaluation system for Ya'an cultivated land, as presented in [Table 1](#).

Model building

BP neural network

A BP neural network is composed of an input layer, a hidden layer, and an output layer. In the current study, the number of input layer nodes is seven due to the cultivated land characteristics of the data source and the obtained score. Meanwhile, the output is 1, which represents the quality score of cultivated land. When the number of neurons in the hidden layer is suitable, better results can be obtained ([Karsoliya, 2012](#)). The selection of the number of hidden layer nodes is presented in [Eq. \(2\)](#):

$$n = \sqrt{a + b} + c, \quad (2)$$

where n , a , and b represent the numbers of hidden layer nodes, input layer nodes, and output layer nodes, respectively; and c represents an integer between 1 and 10.

Therefore, the mean square error (MSE) of the model results at different numbers of hidden layer nodes is adopted, as shown in [Table 2](#).

As indicated by the result, the effect of the model is the best when the number of hidden layers is five. In the BP model, the optimiser used is Adam, the learning rate is 0.01, the maximum training time is 500, and batch size is 100. Thus, the establishment of the BP neural network model is completed, as illustrated in [Fig. 1](#).

AM

Attention is one of the most important components of neural networks that are adept at understanding sequences, including video sequences, action sequences in real life, or a sequence of inputs, such as voice, text, or any other data. Obtaining a reasonable vector representation is typically difficult because the input sequence of long short-term memory or a recurrent neural network may be too long. Thus, AM is created. The attention mechanism not only greatly improves the efficiency and accuracy of perceptual information processing, but also provides the interpretability for the model generation process ([Niu, Zhong & Yu, 2021](#)). At present, the application of AM to the field of agriculture is gradually becoming popular ([Zhao et al., 2021](#); [Zhao, Huang & Nie, 2021](#)). However, it has no relevant application to cultivated land quality.

AM was proposed by [Bahdanau, Cho & Bengio \(2014\)](#). Its original purpose was to automatically search relevant parts from the input sequence of the current predictor by constructing a mechanism. These authors used AM to build a better translation model, proving that AM is reasonable.

To understand AM, we can divide it into three steps: score function, alignment function, and generate context vector function.


Score Function: The similarity between the environment vector and the current input vector is measured. The important input information that should be focused on in the current environment is identified. These authors used AM to build a better translation

Table 1 Cultivated land quality evaluation index system in Yucheng District.

Factor	Level 1		Level 2		Level 3		Level 4		Level 5		Level 6	
	Index value	Score	Index value	Score	Index value	Score	Index value	Score	Index value	Score	Index value	Score
Surface soil texture	Loam	6	Clay	4	Sand	2	Gravelly Soil	1				
Soil organic matter	≥ 40	6	[30, 40)	5	[20, 30)	4	[10, 20)	3	[6, 10)	2	<6	1
pH value	[6.0, 7.9)	6	[5.5, 6.0) or [7.9, 8.5)	5	[5.0, 5.5) or [8.5, 9.0)	4	[4.5, 5.0)	3	<4.5 or ≥ 9.0	2		
Natural factor Available P/ppm	≥ 40	6	[20, 40)	5	[10, 20)	4	[5, 10)	3	[3, 5)	2	<3	1
Total nitrogen%	≥ 2	6	[1.5, 2)	5	[1.0, 1.5)	4	[0.75, 1)	3	[0.5, 0.75)	2	<0.5	1
Available K/ppm	≥ 200	6	[150, 200)	5	[100, 150)	4	[50, 100)	3	[30, 50)	2	<30	1
Available N/ppm	≥ 150	6	[120, 150)	5	[90, 120)	4	[60, 90)	3	[30, 60)	2	<30	1

Table 2 The training times and errors of BP neural networks with different hidden layer nodes.

The number of hidden layer node	Training times	MSE
3	30	0.1348
4	30	0.1596
5	30	0.0926
6	30	0.0976
7	30	0.1855
8	30	0.1171
9	30	0.0996
10	30	0.0961
11	30	0.1514
12	30	0.1105

**Figure 1** Quality evaluation of cultivated land based on the BP neural network.

Full-size DOI: 10.7717/peerjcs.948/fig-1




Figure 2 Attention mechanism.

Full-size DOI: 10.7717/peerjcs.948/fig-2

model, proving that AM is reasonable. The structure of AM is shown in Fig. 2. The calculation method is presented in Eq. (3):

$$e_{ij} = a(c, h_i) = v_a^T \tanh(W_a * c + U_a * h_i), \quad (3)$$

where e_{ij} is the alignment model that is used to measure the alignment of the j -th word at the input position to the i -th word at the output position. a and c represent the alignment model function and the context vector. h_i is the input. v_a , W_a and U_a are the weight matrices.

Alignment Function: Attention weight is calculated. Softmax is typically used for normalisation. The calculation method is presented in Eq. (4):

$$\alpha_{ij} = \frac{\exp(e_{ij})}{\sum_{k=1}^{T_x} \exp(e_{ik})}, \quad (4)$$

where T_x represents the last symbol of the input vector.

Generate Context Vector Function: The output vector is obtained with the attention weight. The calculation method is presented in Eq. (5):

$$z_{ij} = \sum_i \alpha_{ij} * h_i. \quad (5)$$

Ensemble model

The ensemble model imports the data trains multiple models and integrates one model by a certain method. It is easy to understand, simple and efficient. This method is one of the common approaches for improving the model effect. The methods for the ensemble model are generally divided into voting, averaging, boosting, and stacking. In the current study,

we use the averaging method to obtain the result, as shown in Eq. (6):

$$\text{result} = \sum_{i=1}^n \text{Weight}_i * P_i, \quad (6)$$

where n , Weight_i and P_i represent the number of models, model weight, and the predicted value of the model, respectively.

Evaluation index

To evaluate the consistency between predicted and true values, MSE and the determination coefficient (R^2) were used to assess the performance of the models in this study, as shown in Eqs. (7) and (8):

$$\text{MSE} = \frac{1}{n} \sum_{i=1}^n (\hat{y}_i - y_i)^2, \quad (7)$$

$$R^2 = \frac{\sum_{i=1}^n (y_i - \bar{y}_i)^2}{\sum_{i=1}^n (\hat{y}_i - \bar{y}_i)^2}, \quad (8)$$

where n is the total number of samples, and \hat{y}_i , y_i and \bar{y}_i represent the predicted values of i -th sample, the true values of the i -th sample and the average values of the total samples.

Laboratory environment

This research is completed using a Windows 10 operating system and a TensorFlow 2.0 framework. The experimental hardware environment is an HP8574 motherboard. The CPU model is Intel Core i7 9750H. The GPU model is NVIDIA GeForce GTX 1660 Ti 6G. The software environment is CUDA 10.0, CUDNN 7.6.5, and Python 3.7.

RESULTS

Results of different machine learning methods

Machine learning has five characteristics: accuracy, automation, speed, customisation and scale. It is applied in our daily lives. To test the effect of the machine learning model on farmland datasets and the subsequent ensemble model, 2150 samples from the datasets are used to train 13 machine learning algorithm models, whilst 920 samples are used for testing. The 13 algorithms are as follows: a gradient boosting, extreme gradient boosting (XGBoost), decision tree, linear regression, support vector regression (SVR), k -nearest neighbour (k -NN), random forest regression, adaptive boosting (AdaBoost), bootstrap aggregating, extreme tree regression, lasso regression, ridge regression and light gradient boosting machine (LightGBM). They respectively correspond to GB, Xgboost, DT, LR, SVR, k -NN, RFR, AdaB, Bag, ET, Lasso, Ridge, and Lgb in Fig. 3. The MSE of each model on the test set is obtained. The result is presented in Fig. 3.

As shown in Fig. 3, the k -NN model exhibits the best effect and the minimum MSE. It is more favourable for the subsequent model fusion to reduce MSE. It is selected as one of the subsequent model fusion algorithms.




Figure 3 Performance of different machine learning models on testing set.

Full-size DOI: [10.7717/peerjcs.948/fig-3](https://doi.org/10.7717/peerjcs.948/fig-3)

Comparison of model effects

To integrate AM into the model, we combine the model with the characteristics of AM, as shown in Fig. 4. In the current study, the attention layer is designed to have two layers: a softmax layer and a multiply operation. The softmax layer, which is added after the input layer, can obtain attention scores and then multiply the scores by the input.

As a common practice in machine learning, data are divided into 2150 training samples and 920 test samples. The other parameters are the same except for the different network structures. These parameters are applied to the BP and AM-BP models. The results are presented in Fig. 5. The AM-BP model is better than the BP model. The MSE is reduced by approximately 0.002 (approximately 12%), the R^2 is increased by approximately 0.005 at the same time.

The MSEs of the BP and AM-BP models on the test set is provided in Table 3. They show that the model with AM is more sensitive to data and exhibits a better learning effect. The AM-BP model also has shortcomings. It allocates attention through weights, which increases the complexity of the network. In addition, the sequential relationship in input cannot be learned by the model.

The AM-BP model can return the value of the attention score, as shown in Fig. 6. In this figure, pH, SST, TN, AN, AP, AK, and SOM correspond to pH value, surface soil texture, total nitrogen, available nitrogen, available phosphorus, available potassium, and soil organic matter, respectively.

When the score is higher, the correlation between the model and related items is higher. As shown in Fig. 6, soil texture and alkali-hydrolysable nitrogen exert more important influences on the score. Soil texture directly affects the physical and chemical properties and fertility status of the soil. For example, loam soil exhibits better cultivability and fertility, and its capability to supply and maintain fertilizer is moderate. It is most suitable for the




Figure 4 Quality evaluation of cultivated land based on the AM-BP neural network.

Full-size DOI: 10.7717/peerjcs.948/fig-4





Figure 5 Performance comparison of BP and AM-BP on the training set.

Full-size DOI: 10.7717/peerjcs.948/fig-5

Table 3 Performance comparison of BP and AM-BP on the testing set.

Model	MSE	R2
BP	0.0162	0.9683
AM-BP	0.0143	0.9726

**Figure 6** The results of attention score.

Full-size DOI: 10.7717/peerjcs.948/fig-6

growth of fruit trees and vegetables. The cultivability and fertility of clay are worse than those of loam. Large pores are lacking between soil particles, and air and water permeability are poor. Clay is more suitable for planting rice.

Effects of ensemble model

In general, when the learner's appointment is more accurate and diversified, its integration is better. To improve the accuracy of the model further, the k -NN, BP, and AM-BP models are fused, and the result is presented in Fig. 7. mix1, mix2, mix3, and mix4 are the results of the fusion of the k -NN, BP, and AM-BP models with certain weights, as shown in Table 4. In addition to the mix1 and mix2 model, the accuracy of the two other models is significantly improved.

DISCUSSION

The result of the cultivated land quality rating obtained using the AM-BP model is presented in Fig. 8. In this figure, the arable land in Yucheng District is divided into four levels. Among which, the third and fourth classes are large, accounting for approximately 80%, followed by the second class. With an extensive area of medium- and low-yield fields, the arable land in Yucheng District exhibits low quality and should be improved. To effectively protect cultivated land resources, improve the quality of cultivated land, and ensure the sustainable development of agriculture, supervision and management should be strengthened, the quality monitoring and early warning system of cultivated land should be improved and the quantity and quality information of land should be updated regularly to capture changes in fertility accurately and perform better in the allocation




Figure 7 The effect of the ensemble model.

Full-size DOI: 10.7717/peerjcs.948/fig-7

Table 4 Types of ensemble model and the weights of the models.

Model names	BP	AM-BP	KNN
Mix 1	0.6	–	0.4
Mix 2	–	0.6	0.4
Mix 3	0.4	0.6	–
Mix 4	0.2	0.6	0.2

and improvement of arable land resources. Relevant departments can develop the quality of cultivated land by providing technical guidance and services to farmers, whilst relying on campaigns, such as soil testing and formula fertilisation, and the transformation of medium- and low-yield soil, to adopt measures to local conditions and rational farming, and thus, realise the sustainable development and utilisation of cultivated land resources. In this study, the model error is reduced and performance is improved by fusing the models. The ensemble model based on the AM-BP model obtained in this study is better than the traditional method, and MSE is significantly reduced. Although this method exhibits good performance, it still has shortcomings. The effect of the ensemble model is not evident compared with that of the AM-BP model. The subsequent research can further improve the result of the model through network pruning and knowledge distillation.

Moreover, the initial parameters of the AM-BP model are zero. It may affect the model's accuracy. Therefore, we will add parameter optimization algorithms to improve the efficiency and stability of the AM-BP model in the next stage of the study.




Figure 8 The results of Arable land quality rating.

Full-size DOI: 10.7717/peerjcs.948/fig-8

CONCLUSIONS

To determine the cultivated land quality rating in the Yucheng District of Ya'an City, a method based on a BP neural network is proposed in the current study. Combined with the situation of data, there are many experimental studies performed for this study, adjusting the structure and parameters of the network. The conclusions are as follows: (1) The AM-BP model with MSE of 0.0143 were more reliable than machine learning models. (2) The accuracy of the ensemble model significantly improved, further implying that the AM-BP model could be applied to accurately mapping cultivated land quality at the regional scale in the future. (3) The quality of cultivated land in Yucheng District is generally good, *i.e.*, mostly third and fourth grades. It conforms to the normal distribution. The land needed to be improved.

ACKNOWLEDGEMENTS

We would like to thank Professor Wei for his useful comments on the paper and Mrs. Ye for providing the data.

ADDITIONAL INFORMATION AND DECLARATIONS

Funding

This work was supported by the CERNET Next Generation Internet Technology Innovation Project of China (No. NGII20170605), the Sichuan Province Department of Education (Grant NO. JG2021-464). The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

Grant Disclosures

The following grant information was disclosed by the authors:

CERNET Next Generation Internet Technology Innovation Project of China: NGII20170605.

Sichuan Province Department of Education: JG2021-464.

Competing Interests

The authors declare there are no competing interests.

Author Contributions

- Yulin Liu performed the experiments, analyzed the data, performed the computation work, prepared figures and/or tables, authored or reviewed drafts of the paper, and approved the final draft.
- Jiaolong Li performed the computation work, prepared figures and/or tables, and approved the final draft.
- Chuang Liu analyzed the data, authored or reviewed drafts of the paper, and approved the final draft.
- Jiangshu Wei conceived and designed the experiments, authored or reviewed drafts of the paper, and approved the final draft.

Data Availability

The following information was supplied regarding data availability:

The raw data and code are available in the [Supplementary Files](#).

Supplemental Information

Supplemental information for this article can be found online at <http://dx.doi.org/10.7717/peerj-cs.948#supplemental-information>.

REFERENCES

- Bahdanau D, Cho K, Bengio Y. 2014.** Neural machine translation by jointly learning to align and translate. ArXiv preprint. [arXiv:1409.0473](https://arxiv.org/abs/1409.0473).
- Deng X, Huang J, Rozelle S, Zhang J, Li Z. 2015.** Impact of urbanization on cultivated land changes in China. *Land Use Policy* **45**:1–7 DOI [10.1016/j.landusepol.2015.01.007](https://doi.org/10.1016/j.landusepol.2015.01.007).
- Ding Y, Peng J. 2018.** Impacts of urbanization of mountainous areas on resources and environment: based on ecological footprint model. *Sustainability* **10**(3):765 DOI [10.3390/su10030765](https://doi.org/10.3390/su10030765).

- Finn C, Abbeel P, Levine S. 2017.** Model-agnostic meta-learning for fast adaptation of deep networks. *International Conference on Machine Learning* 17:1126–1135. Available at <https://arxiv.org/pdf/1703.03400.pdf>.
- Gao H, Yang W, Wang J, Zheng X. 2021.** Analysis of the effectiveness of air pollution control policies based on historical evaluation and deep learning forecast: a case study of Chengdu-Chongqing region in China. *Sustainability* 13(1):206 DOI 10.3390/su13010206.
- Hao J, Lin Y, Ren G, Yang G, Han X, Wang X, Ren C, Feng Y. 2021.** Comprehensive benefit evaluation of conservation tillage based on BP neural network in the Loess Plateau. *Soil and Tillage Research* 205:104784 DOI 10.1016/j.still.2020.104784.
- Hu T, Zhao J, Zheng R, Wang P, Li X, Zhang Q. 2021.** Ultrasonic based concrete defects identification via wavelet packet transform and GA-BP neural network. *PeerJ Computer Science* 7:e635 DOI 10.7717/peerj-cs.635.
- Karsoliya S. 2012.** Approximating number of hidden layer neurons in multiple hidden layer BPNN architecture. *International Journal of Engineering Trends and Technology* 3(6):714–717.
- Lin C, Hu Y, Liu Z, Peng Y, Wang L, Peng D. 2022.** Estimation of cultivated land quality based on soil hyperspectral data. *Agriculture* 12(1):93 DOI 10.3390/agriculture12010093.
- Liu H, Liu J, Yang W, Chen J, Zhu M. 2020a.** Analysis and prediction of land use in Beijing-Tianjin-Hebei region: a study based on the improved convolutional neural network model. *Sustainability* 12(7):3002 DOI 10.3390/su12073002.
- Liu S, Peng Y, Xia Z, Hu Y, Wang G, Zhu A, Liu Z. 2019.** The GA-BPNN-based evaluation of cultivated land quality in the PSR framework using Gaofen-1 satellite data. *Sensors* 19(23):5127 DOI 10.3390/s19235127.
- Liu Y, Zhang Y, Guo L. 2010.** Towards realistic assessment of cultivated land quality in an ecologically fragile environment: a satellite imagery-based approach. *Applied Geography* 30(2):271–281 DOI 10.1016/j.apgeog.2009.07.002.
- Liu L, Zhou D, Chang X, Lin Z. 2020b.** A new grading system for evaluating China's cultivated land quality. *Land Degradation & Development* 31(12):1482–1501 DOI 10.1002/ldr.3547.
- Nassar L, Okwuchi IE, Saad M, Karray F, Ponnambalam K. 2020.** Deep learning based approach for fresh produce market price prediction. In: *2020 International Joint Conference on Neural Networks (IJCNN)*. 1–7 DOI 10.1109/ijcnn48605.2020.9207537.
- Niu Z, Zhong G, Yu H. 2021.** A review on the attention mechanism of deep learning. *Neurocomputing* 452:48–62 DOI 10.1016/j.neucom.2021.03.091.
- Pabón OS, Montenegro O, Torrente M, González AR, Provencio M, Menasalvas E. 2022.** Negation and uncertainty detection in clinical texts written in Spanish: a deep learning-based approach. *PeerJ Computer Science* 8:e913 DOI 10.7717/peerj-cs.913.
- Smith P, Clark H, Dong H, Elsiddig EA, Haberl H, Harper R, House J, Jafari M, Masera O, Mbow C, Ravindranath NH. 2014.** Agriculture, forestry and other land use (AFOLU). Available at http://pure.iiasa.ac.at/id/eprint/11115/1/ipcc_wg3_ar5_chapter11.pdf.

- Sun J, Pan L, Tsang DC, Zhan Y, Zhu L, Li X. 2018.** Organic contamination and remediation in the agricultural soils of China: a critical review. *Science of the Total Environment* **615**:724–740 DOI [10.1016/j.scitotenv.2017.09.271](https://doi.org/10.1016/j.scitotenv.2017.09.271).
- Tan Y, Chen H, Lian K, Yu Z. 2020.** Comprehensive evaluation of cultivated land quality at county scale: a case study of Shengzhou, Zhejiang Province, China. *International Journal of Environmental Research and Public Health* **17**(4):1169 DOI [10.3390/ijerph17041169](https://doi.org/10.3390/ijerph17041169).
- Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, Kaiser Ł, Polosukhin I. 2017.** Attention is all you need. In: *Advances in neural information processing systems*. 30.
- Viana CM, Santos M, Freire D, Abrantes P, Rocha J. 2021.** Evaluation of the factors explaining the use of agricultural land: a machine learning and model-agnostic approach. *Ecological Indicators* **131**:108200 DOI [10.1016/j.ecolind.2021.108200](https://doi.org/10.1016/j.ecolind.2021.108200).
- Wang H, Li W, Huang W, Nie K. 2020.** A multi-objective permanent basic farmland delineation model based on hybrid particle swarm optimization. *ISPRS International Journal of Geo-Information* **9**(4):243 DOI [10.3390/ijgi9040243](https://doi.org/10.3390/ijgi9040243).
- Xie X, Zheng S, Hu Y, Guo Y. 2018.** Study on the method of cultivated land quality evaluation based on machine learning. In: *2018 Fifth International Workshop on Earth Observation and Remote Sensing Applications (EORSA)*. 1–5 DOI [10.1109/eorsa.2018.8598544](https://doi.org/10.1109/eorsa.2018.8598544).
- Zhao X, Huang L, Nie Y. 2021.** Temperature prediction based on integrated deep learning and attention mechanism. In: *2021 IEEE 6th International Conference on Computer and Communication Systems (ICCCS)*. Piscataway: IEEE, 163–167 DOI [10.1109/ICCCS52626.2021.9449176](https://doi.org/10.1109/ICCCS52626.2021.9449176).
- Zhao S, Peng Y, Liu J, Wu S. 2021.** Tomato leaf disease diagnosis based on improved convolution neural network by attention module. *Agriculture* **11**(7):651 DOI [10.3390/agriculture11070651](https://doi.org/10.3390/agriculture11070651).
- Zhu M, Liu S, Xia Z, Wang G, Hu Y, Liu Z. 2020.** Crop growth stage gpp-driven spectral model for evaluation of cultivated land quality using GA-BPNN. *Agriculture* **10**(8):318 DOI [10.3390/agriculture10080318](https://doi.org/10.3390/agriculture10080318).