

# Speeding-Up Mutation Testing via Data Compression and State Infection

Qianqian Zhu

Delft University of Technology

Email: qianqian.zhu@tudelft.nl

Annibale Panichella

University of Luxembourg

Email: annibale.panichella@uni.lu

Andy Zaidman

Delft University of Technology

Email: a.e.zaidman@tudelft.nl

**Abstract**—Mutation testing is widely considered as a high-end test criterion due to the vast number of mutants it generates. Although many efforts have been made to reduce the computational cost of mutation testing, its scalability issue remains in practice. In this paper, we introduce a novel method to speed up mutation testing based on state infection information. In addition to filtering out uninfected test executions, we further select a subset of mutants and a subset of test cases to run leveraging data-compression techniques. In particular, we adopt Formal Concept Analysis (FCA) to group similar mutants together and then select test cases to cover these mutants. To evaluate our method, we conducted an experimental study on six open source Java projects. We used EvoSuite to automatically generate test cases and to collect mutation data. The initial results show that our method can reduce the execution time by 83.93% with only 0.257% loss in precision.

## I. INTRODUCTION

Mutation testing is a fault-based testing technique that has been very actively investigated by researchers since the 1970s. Mutation testing introduces small syntactic changes into the program to generate faulty versions (mutants) according to well-defined rules (mutation operators) [1]. Then the quality of a test suite can be qualified as the percentage of mutants it distinguishes from the original program (mutation score). The benefits of mutation testing have been shown in many empirical studies, e.g. [2], [3].

Despite its well-known advantages, mutation testing is currently not widely applied. This is due to the computation cost incurred from executing each mutation against the test suite to obtain the mutation score and the number of mutants increasing dramatically with the size of the program.

To address these limitations, several methods have been proposed in literature, such as mutant sampling [4] and selective mutation [5]. Differently from the aforementioned methods that are independent of the program under test, other procedures have been developed to optimise further the mutation execution procedure given the program under test. State-of-the-art techniques falling into this category filter unnecessary executions based on the dynamic information at run-time, e.g., line coverage [6] and state infection [7].

In this paper, we further optimise mutation execution using data compression techniques based on state infection information. In addition to filtering out unnecessary test executions, we “compress” mutation execution by selecting a subset of mutants and a subset of test cases to estimate the mutation

score with minimal loss of precision. We coined our method “ComMT”, which is short for Compressed Mutation Testing.

## II. RELATED WORK

The most well-known techniques for reduction of the computational cost are mutant sampling [4], selective mutation [5], weak mutation [8] and mutant schema [9]. However, these methods are independent of the program under test. More recent researchers are targeting to further improve the mutation execution process by gathering information from the program at run-time. A widely adopted strategy in this category is to execute the test suite on the original program before mutation execution to avoid unnecessary executions. Coverage-based optimisation filters out the test executions when a test case does not cover the mutated statement; this optimisation has been used in existing mutation testing tools, such as JAVALANCHE [6], Major [10] and PIT/PiTest [11]. Also of interest is infection-based optimisation, which only executes a test case on a mutant when the test infects the execution state of the mutant, filtering out weakly live mutants. Just et al. [7] improved the original infection-based method by combining propagation information: a test must be executed on a mutant if the execution state of the mutated expression propagates to a top-level expression. In the meanwhile, they partitioned mutants based on their intermediate results for each test case. Also, Ma and Kim [12] applied a similar idea to cluster mutants for each test case by comparing the values of innermost expressions. Unfortunately, infection-based optimisation has not been publicly integrated into existing mutation tools.

Mutant clustering is another approach considering the program under test. It aims to reduce the number of mutants based on the similarity of mutants instead of random sampling. It is introduced by Hussain [13] who applied clustering algorithms (e.g. K-means) to assemble similar mutants. However, their methods require the execution of all mutants against all the test cases, which cannot reduce the runtime overhead during the mutation execution. Later, Ji et al. [14] measured the similarity of the mutants using domain analysis. They can divide mutants directly based on static control flow analysis. But they only manually analysed the clustering accuracy without indication of the runtime overhead caused by domain analysis.

Our method is a combination of infection-based optimisation and mutant clustering. We group mutants based on




Fig. 1. Mutation data compression

their state infection outcomes which are different from Hus-sain [13]. To find the groupings of mutants, we only require one execution of the test suite on the original program. Furthermore, compared to Just et al. [7] and Ma and Kim [12]’s work, we partition mutants for all test cases instead of targeting each test case. Thus, we can further reduce the number of test cases with test selection techniques. Meanwhile, our method can also be combined with other cost reduction techniques which require no knowledge of the program under test, such as selective mutation and mutant schema.

### III. MUTATION DATA COMPRESSION

In *weak* mutation testing, a mutant is *killed* if its execution leads to a state change, i.e., the values of variables and class attributes after the mutated expression differ from the values in the original class. For example, the expression  $c=a*b$  and its mutated version  $c=a/b$  have different outcomes (i.e., the mutant is weakly killed) if  $a \neq 1$  and  $b \neq 1$ . Differently from *strong* mutation, *weak* mutation scores can be computed with one single execution of each test by instrumenting the mutated locations to keep track of the execution states [15]. Therefore, it is widely used as a light-weight mutation score.

*ComMT* uses weak mutation (or infection state) and data compression techniques to decide which mutants and which tests to consider for strong mutation. The overall methodology of ComMT consists of five stages as illustrated in Figure 1:

- **Instrumentation.** We generate mutants for the program under analysis relying on the internal mutation engine in EvoSuite [15]. Then, we instrument the original program to keep track of the mutation locations.
- **Test execution.** Once instrumented, the test suite is executed once to collect data of the infected mutants. In other words, in this stage we record the mutants that are weakly killed by the tests.
- **Infection analysis.** The results of the previous stage are stored in the *mutant-by-test infection* matrix. Let  $P$  be the program under analysis and let  $\mathbb{T}$  be the test suites; let  $\mathbb{M}$  be the set of mutants for the programs  $P$  generated by preselected mutation operators. A *mutant-by-test infection* matrix is a  $m \times n$  matrix where  $m$  is the number of mutants,  $n$  is the number of test cases in  $T$ , and a generic entry  $x_{i,j}$  is a binary value indicating whether the  $i$ -th mutant is weakly killed (i.e.,  $x_{i,j} = 1$ ) or not (i.e.,  $x_{i,j} = 0$ ) by the  $j$ -th test  $\in T$ .

- **Formal Concept Analysis (FCA).** FCA is applied on the *mutant-by-test infection* matrix in order to extract the hidden relationships (formal concepts) among mutants and tests according to the infection data.
- **Data compression.** The extracted concepts are then used to *compress* the *mutant-by-test infection* matrix. The resulting matrix has a lower number of rows and columns compared to the original one: the rows denote groups of mutants belonging to the same formal concepts; similarly, tests are grouped by concepts to form the columns. Such a compressed matrix is used then to select mutants and tests for the strong mutation analysis.

The details of FCA and the data compression procedure are described in details in the next sub-sections.

#### A. FCA grouping

Starting from the mutant-by-test matrix, we analyse the *conceptual structures* among mutants and tests using FCA. FCA is a data analysis method which has been shown to be a powerful mathematical technique to convey and summarise large amounts of information [16]. It takes as input the *formal context* which is a structure  $C = (O, A, I)$  where  $O$  is the set of *objects*,  $A$  is the set of *attributes* while  $I \subseteq O \times A$  is a binary relation between  $O$  and  $A$ . Then, FCA produces the *concept lattice*, which is a collection of *formal concepts* in the data ordered by *sub-concept* relations, i.e., from super-concepts to sub-concepts. Each *formal concept* is composed by (i) a group of objects sharing the same attributes, and (ii) all attributes that apply to the objects in the concept [16].

In our context, the objects in  $O$  are the mutants, the attributes in  $A$  are the test cases, and  $I$  is our mutant-by-test matrix. Then, FCA derives formal concepts that represent groups of mutants that are weakly covered by the same subset of tests. In other words, the output of FCA can be viewed as two-way clustering since mutants and tests are grouped in concepts such that all mutants in the same concept  $c$  are weakly covered by all tests in  $c$ .

To provide a more practical description, let us consider the mutant-by-test matrix with six mutants and four tests reported in Figure 2. The mutant-by-test matrix can be viewed as a *formal context* for FCA with  $O = \{m_1, m_2, m_3, m_4, m_5, m_6\}$ ,  $A = \{t_1, t_2, t_3, t_4\}$  and  $I$  corresponding to the matrix entries. For this example, FCA returns the *concept lattice* depicted in the right side of Figure 2. We can observe that FCA derives one formal concept with mutants  $\{m_5, m_6\}$  and tests  $\{t_1, t_2\}$  meanings that the two mutants can be weakly covered by both the two tests. While  $m_5$  and  $m_6$  are not necessary equivalent mutants, we may argue that if  $t_1$  (or  $t_2$ ) kills  $m_5$  then it likely kills  $m_6$  as well in strong mutation. Therefore, for this concept we can select only one mutant (e.g.,  $m_5$ ) or/and one test (e.g.,  $t_1$ ) to represent the whole concept.

Among all concepts in the formal lattice, we select for data compression only those that are directly connected to the exit point in the lattice hierarchy that we refer to as *maximal groupings*. In our example in Figure 2, there are three maximal groupings, which are  $\{m_5, m_6|t_1, t_2\}$ ,  $\{m_4|t_3\}$ , and  $\{m_3|t_4\}$ .




Fig. 2. A toy program and its concept lattice

The other concepts in the lattice (e.g.,  $\{m_2, m_5, m_6 | t_1\}$  in Figure 2) are already included in the maximal grouping by *sub-concept* relation which is graphically represented by the hierarchy in the lattice. Then, the maximal groupings are used to compress the mutant-by-test matrix by condensing the rows of mutants from the same maximal group into one single row that represents the whole concept. A similar compression can be performed on the columns of the mutant-by-test matrix according to how tests are grouped in maximal groupings. Using this compressed matrix we can reduce the number of mutants and tests to run for strong mutation analysis.

### B. Test case selection

After obtaining the maximal groupings from the concept lattice, we first compress the mutant-by-test matrix by condensing the rows, i.e., we select one mutant from each maximal grouping to represent the whole set. Then to further perform the compression on the columns, we propose three approaches of test case selection based on preselected mutants:

1) *FCA-based selection*: In each formal concept  $c$ , we have a set of mutants which share a set of attributes, i.e., test cases. Tests in  $c$  weakly kill all mutants in the same concept  $c$ , from which follows our assumption that tests in the same concepts also exhibit similar behaviour. Thus, we select one test from each formal concept to further condense the columns of the original matrix. More specifically, this strategy is a rigid way to bi-cluster the mutant-by-test matrix based on maximal groupings of the concept lattice.

2) *Set cover using greedy algorithm*: After selecting one mutant from each maximal grouping, instead of condensing the columns by FCA-based selection, we come up with another idea: to find a sufficient subset of test cases that weakly kill all possible mutants. This becomes the set cover problem. Considering that the set cover problem is a well-known NP-hard problem, we adopt a greedy algorithm for polynomial time approximation of this problem. Based on our assumptions in Section III-A, if one test can weakly kill one mutant in a maximal grouping, then the test is very likely to weakly kill the rest. Thus, we consider one maximal grouping as one element to be covered in set cover problem. Here comes our set cover-based selection: at each stage, we choose the test that weakly kills the largest number of *uncovered* maximal groupings.

3) *Sorting by maximal groupings*: Instead of selecting a minimal subset of test cases that weakly kill all the possible mutants, we sort the test cases by the number of maximal groupings it belongs. The key idea behind this strategy is: test

TABLE I  
SUBJECT PROGRAMS

Project	Full name	LOC	# Classes	# Test cases	# Mutants	# Killed mutants
jsecurity	Jsecurity	13,135	197	313	2,384	2,036
summa	summa	69,339	512	470	8,201	3,895
db-everywhere	DB-Everywhere	7,125	97	84	302	168
noen	dynamic analysis & test	18,867	382	767	5,222	4,069
jtailgui	JTailPlus	2020	43	147	1246	776
caloriecount	CalorieCount	61,544	596	4,699	49,925	26,122
Overall		172,030	1,827	6,480	67,280	37,066

cases belonging to more maximal groupings means they can weakly cover more mutants, thereby, they are more likely to strongly kill more mutants. In particular, we select the test cases with the largest number of maximal groupings at each stage until all the possible mutants are covered.

## IV. EXPERIMENTAL STUDY

To evaluate the effectiveness of our method, we conduct an initial experimental study on a set of open source programs. In the following sections, we describe our experimental setup.

### A. Research questions

We first explored whether FCA is suitable for compressing the infection matrix. This leads to:

**RQ1:** *Can FCA find maximal groupings in the infection matrix?*

After generating the maximal groupings, we set out to investigate the similarity of mutants in each maximal grouping, especially their outcomes in terms of strong mutation. **RQ2** addresses exactly this:

**RQ2:** *How frequently do mutants in a maximal grouping generated by FCA have same outcome in strong mutation?*

To further compress the mutation data, in **RQ3** we examine test case selection based on FCA grouping to cover the selected mutants:

**RQ3:** *Does test case selection based on FCA grouping yield a smaller number of tests on average?*

Our method's aim is to reduce execution time while maintaining the precision of mutation testing. This leads to **RQ4**:

**RQ4:** *What is the trade-off between the mutation score and the execution time using ComMT?*

### B. Subject program

We evaluated ComMT using six open source projects which come from SF110 [17]. Table I shows the basic information of subject programs used in our experimental study.

### C. Experimental setup

To carry out the experiment, we used EvoSuite to automatically generate test cases for each subject programs. EvoSuite supports different criteria to guide the process of test data generation. In our study, we chose *strong-mutation* as the criterion for test data generation. The main reason here is that we can make use of data from EvoSuite to estimate the effectiveness of our method. More specifically, to target the strong-mutation criterion, EvoSuite creates mutants using its




Fig. 3. Overall workflow of experimental study

own embedded mutation operators and guides the test data generation to kill these mutants. At the end of test data generation, the target coverage information from EvoSuite can be used as the result of mutation testing. Furthermore, infection is part of the fitness function for the strong-mutation criterion. Therefore, we can obtain the infection matrix by collecting the fitness function values. Besides, we can collect the average execution time of test cases from EvoSuite; this is used to estimate the execution time of mutation testing. The overall workflow of the test data generation and data collection from EvoSuite can be seen in Figure 3. After obtaining the infection matrix, we applied ConExp [18] for FCA processing.

To answer **RQ1** we use ConExp to build the concept lattices from the infection matrix and then extract the maximal groupings. We then calculate the number of mutants in each maximal grouping and we summarise the size of the maximal groupings across all projects to determine whether FCA is suitable for compressing the infection matrix.

To answer **RQ2**, we calculated the approximation result of killed mutants to evaluate the similarity of mutant in strong mutation. Firstly, we randomly select one mutant from each maximal groupings and use the outcome of this mutant in strong mutation (whether the mutant is killed or not) to represent the whole group. To minimise the random error, we carry out the process of the mutant selection 100 times for each project, and compare the error rate in terms of killed mutant number, as shown in Definition 1. For this experiment, we used all test cases.

$$\text{error rate} = \frac{\text{approximation} - \text{actual result}}{\text{actual result}} \quad (1)$$

To answer **RQ3**, we compared three strategies of test case selection (as mentioned in Section III-B) based on the results of FCA. For each subset of test cases generated by ComMT, we mainly analysed its size and the number of killed mutants. For FCA-based test case selection, we need to select one test case from each maximal grouping randomly; we treat each maximal grouping equally. Similarly to **RQ2**, we

TABLE II  
TEST CASE REDUCTION AND MUTANT COMPRESSION

Project	Test case reduction (%)			Mutant compression ratio by FCA		
	Set cover	FCA	Sorting	# Mutants	# Groupings	Compression ratio
jsecurity	67.09	37.23	15.34	2,384	442	5.39
summa	64.26	38.25	17.23	8,201	573	14.31
db-everywhere	73.81	60.71	47.62	302	54	5.59
noen	62.19	40.54	12.91	5,222	738	7.08
jtaiogui	52.38	38.37	24.49	1246	161	7.74
caloriecount	69.16	49.05	25.45	49,925	4,640	10.76
Overall	64.82	44.03	23.84	11,213.33	1,101.33	8.48

ran the process of FCA-based test case selection 100 times independently to eliminate the random error. For set cover-based and sorting-based test case selection, we choose one test case based on previously selected information, so we recorded the test case number and killed mutant number at each iteration.

To answer **RQ4**, we mainly studied the relationship between execution time and error rate when adopting ComMT approach. Here the execution time is estimated by the data collected from EvoSuite. To simulate the actual mutation execution process, test cases are executed depending on the selected sequence. For FCA-based selection, there is no selected sequence, as each maximal grouping is treated equally. So when calculating the execution time for FCA-based selection, we adopted the default sequence in the original test suite. As soon as the mutant is killed by a test case, the rest of the unexecuted test cases are no longer run against this mutant. In order to further quantify the optimisation results from ComMT, we compared our method with other two optimisation configurations as mentioned in Section II, i.e., coverage-based and infection-based optimisation. For these two optimisation approaches and our methods, we need to collect the reachability and necessity condition from a single execution of the whole test suite. In addition to one single execution of the whole test suite, ComMT requires extra time for data compression. Here we do not take data compression into consideration as the compression process is fairly quick (within 10 seconds). Therefore, we assume that the preprocessing overhead of these three methods is similar, and we can simply compare their execution time during the mutation execution procedure.

## V. RESULTS

### A. RQ1: FCA grouping

Table II summarises the number of maximal groupings and the compression ratio for each the project. The compression ratio is defined the number of mutants divided by the number of groupings. We can see that on average there are 8.48 mutants in each maximal grouping; this means FCA can compress the original size of mutants by 88.2%. Thereby, we can conclude that FCA can find the maximal groupings from infection matrix and also significantly reduce the number of mutants that need to be executed.

### B. RQ2: mutant similarity

To quantify the similarity of mutants in each maximal grouping, we compared the approximation result of mutant sampling to the actual results. We plotted the sampling results in Figure 4 using box plots. The error rate of the approximation results can be both positive (overestimation) or negative (underestimation). This is caused by the overall trend: whether the randomly selected mutant from each FCA grouping overestimates the killed mutants for the whole grouping or not. The average error rate is around zero among all the projects; this shows that the mutants in a maximal grouping exhibit similar behaviours in strong mutation on average. Moreover, the mutants in a maximal grouping are the ones whose execution states are infected by the same group of test cases. In terms of weak mutation, these mutants are killed by a same group of test cases; this leads to an interesting finding: mutants which have the same outcome in weak mutation against all the test cases (weakly equivalent) are very likely to have the same outcome in strong mutation.

However, the error rate distribution varies greatly between projects: for project `jtaiogui` it varies most, ranging from -33.1% to 39.9%. For projects `noen` and `caloriecount`, which are relatively small systems, the distribution ranges between respectively -4.9% to 6.6% and -7.9% to 7.2%. We speculate that this difference is due to the size of the original test cases. We group mutants by observation from their weak mutation behaviour against the test cases. What we do in fact is to judge whether two mutants are equivalent in terms of weak mutation, which is a typical undecidable problem. Therefore, the confidence of whether mutants are weakly equivalent is determined by how many test cases are involved during the judgement. This reveals a potential limitation of the FCA groupings approach: projects with a relatively small test suite are more likely to have low clustering accuracy.

### C. RQ3: test case selection

We summarised the detailed iteration results of three test case selection strategies in Figure 5. Test case selection based on FCA generates a solution distributed in the small area: its test case number is around a constant value, and the average of killed mutant number is near the actual results. For set cover-based selection, the killed mutant number initially grows quickly as the test case number increases. As soon as the mutants are all covered by the selected test cases, the method stops adding new test cases, thus ending up with a relatively small set of test cases. However, we can see the optimal solution generated by the set cover-based selection can never reach to actual results. This reflects that a minimum set of test cases that weakly kills all the mutants is not enough to predict the strong mutation score. The sorting-based selection has the same trend as the set cover-based one: it increases slowly compared to the set cover-based strategy, but it reaches the actual results in the end.

Table II summarises the comparison of the final sub-test suites generated by three strategies in terms of the suite size reduction. For the set cover-based selection, it generates the




Fig. 4. Error rate of mutant selection based on FCA

smallest set of test cases among the three. The FCA-based selection can reduce the test size by 44.03% on average. For the sorting-based selection, the size of the subset is the largest but it can still reduce 23.84% of the original test suite. Together with the observations from Figure 5a, we conclude that test case selection based on FCA grouping yields a smaller number of tests compared to the original test suite.

### D. RQ4: trade-offs

Table III summarises the comparison of three methods in terms of execution time reduction and error rate. To calculate the execution time reduction, we used coverage-based optimisation as a baseline. For the coverage-based optimisation, we see that the execution time ranges from 0.02 to 19.21 minutes. Overall, the infection-based optimisation which uses weak mutation as filtering strategy to select the mutants for strong mutation reduces runtime by 11.37%, while ComMT reaches at least 83.93%, which is a  $\geq 7$  time speed-up.

Moreover, for ComMT, we compared four test case selection strategies based on selected mutants: no selection, set cover-based, FCA-based and sorting-based selection. We observe that ComMT with mutant compression alone achieves a significant reduction in runtime. By applying test case selection based on FCA groupings, the improvement in execution time reduction is small: at most 5.89%.

With regard to the three strategies for test case selection, we see that for set cover-based selection, its execution time is the least, but the loss of precision is the most (-19.36%). FCA-based selection reduces execution time by 86.84%, while the error rate is -4.76%. For sorting-based selection, the execution time is the largest, but its error rate is the lowest, almost equalling the actual results. Comparing sorting-based selection to the situation without test case selection, we can see the error rate is similar, but the execution time is slightly less (0.58%). One thing must be noted: we select test cases based on mutants grouped by FCA. Thus the error rate of the selected test cases is largely dependent on the selected mutants. When the selected mutants overestimate the killed mutants, i.e., the error rate of the approximation is positive, less test cases (causes negative impact on error rate) might achieve a slight improvement in the overall error rate. Take project `summa` for example: without any test case selection, the overall error rate is 0.74%. After applying sorting-based test case selection,




Fig. 5. Comparison of test case selection in each iteration

TABLE III

TRADE OFFS BETWEEN EXECUTION TIME REDUCTION &amp; ERROR RATE (%)

Project	Cov. based	Inf. based	ComMT									
			No selection				Set cover		FCA		Sorting	
			Exec.	Red.	Red.	Err.	Red.	Err.	Red.	Err.	Red.	Err.
jsecurity	1.39	16.78	87.71	0.13	90.27	-17.42	88.55	-2.46	87.31	-0.04		
summa	1.54	13.57	90.97	0.74	93.58	-14.1	92.18	-2.25	90.87	0.69		
db-everywhere	0.02	3.65	59.29	-0.26	80.81	-18.83	70.43	-6.22	63.95	-0.26		
noen	1.58	6.09	88.52	0.30	91.08	-30.69	89.52	-7.29	87.98	0.14		
jtaiogui	0.31	18.7	87.66	0.07	91.33	-13.11	89.86	-3.42	87.89	0.07		
caloriecount	19.21	9.39	89.44	0.04	91.83	-21.99	90.5	-6.89	89.06	-0.38		
Overall	-	11.37	83.93	0.257	89.82	-19.36	86.84	-4.76	84.51	0.262		

the overall error rate changes to 0.69% which is a 0.05% improvement.

To summarize, ComMT can reduce the execution time by 83.93% using mutant compression alone with only 0.257% precision loss.

## VI. THREATS TO VALIDITY

**Threats to external validity:** First, our experimental study only evaluated our method based on automatically generated test cases from EvoSuite, which might not be generalisable to other (manually written) test suites. Second, our results are based on mutants generated by embedded mutation operators of EvoSuite; this results might be different when using other mutation tools. With regard to subject selection, we chose six open source projects from a well-known corpus (SF110) differing in size and domain.

**Threats to internal validity:** The main threat to internal validity for our study is that there might be faults in our implementation of ComMT and the experiments. As we mainly relied on existing software (EvoSuite and ConExp) and this

software is considered reliable, we reduce internal threats to a large extent. Moreover, we carefully reviewed and tested all code for our study to eliminate faults in our implementation.

**Threats to construct validity:** The main threat to construct validity is the measurement we used to evaluate our methods. To minimise the threat, we used estimated execution time to assess the cost of our techniques. A possible issue is whether the estimated execution time is representative of actual runtime. Yet, as we are only comparing estimated execution times and not actual execution times, the relationship between estimated runtime and actual runtime is less critical. Also, we used error rate to measure the approximation caused by our method.

## VII. CONCLUSION & FUTURE WORK

In this paper, we have presented an approach to speed-up mutation testing using data compression techniques based on state infection information. We have adopted Formal Concept Analysis (FCA) to group the mutants together which have the highest similarity in state infection against all test cases. By analysing the behaviour of mutants grouped by FCA, we found that the mutants in a group show similar behaviours in strong mutation on average. We have further explored the trade-offs between execution time and precision loss by applying FCA to compress mutation testing. The method we have adopted is to select one mutant from each FCA grouping and then select test cases to cover the mutants. The overall results show that our method can reduce the execution time by 83.93%-84.51%, with a loss of precision between 0.257%-0.262% on average. This provides one promising solution to reduce the high computational cost of mutation testing.

While our current results are encouraging, we envision the following future work:

- Generalise to other test suites, e.g. manually written ones.
- Investigate other data compression methods, such as Principal Component Analysis (PCA).
- Implement our method on top of an existing mutation testing tool.
- Examine ways to control the clustering accuracy in the light of small test suites.

## REFERENCES

- [1] J. Offutt, "A mutation carol: Past, present and future," *Information and Software Technology*, vol. 53, no. 10, pp. 1098–1107, 2011.
- [2] A. P. Mathur and W. E. Wong, "An empirical comparison of data flow and mutation-based test adequacy criteria," *Software Testing, Verification and Reliability*, vol. 4, no. 1, pp. 9–31, 1994.
- [3] J. H. Andrews, L. C. Briand, and Y. Labiche, "Is mutation an appropriate tool for testing experiments?" in *Proc. Int'l Conf Software Engineering (ICSE)*. IEEE, 2005, pp. 402–411.
- [4] A. T. Acree Jr, "On mutation." DTIC Document, Tech. Rep., 1980.
- [5] A. J. Offutt, A. Lee, G. Rothermel, R. H. Untch, and C. Zapf, "An experimental determination of sufficient mutant operators," *ACM Trans. Softw. Eng. Methodol.*, vol. 5, no. 2, pp. 99–118, 1996.
- [6] D. Schuler and A. Zeller, "Javalanche: efficient mutation testing for java," in *Proc. ESEC/FSE*. ACM, 2009, pp. 297–298.
- [7] R. Just, M. D. Ernst, and G. Fraser, "Efficient mutation analysis by propagating and partitioning infected execution states," in *Int'l Symp. on Software Testing and Analysis (ISSTA)*. ACM, 2014, pp. 315–326.
- [8] W. E. Howden, "Weak mutation testing and completeness of test sets," *IEEE Trans. Software Eng.*, no. 4, pp. 371–379, 1982.
- [9] R. H. Untch, "Mutation-based software testing using program schemata," in *Proc. annual Southeast regional conf.* ACM, 1992, pp. 285–291.
- [10] R. Just, F. Schweiggert, and G. M. Kapfhammer, "MAJOR: An efficient and extensible tool for mutation analysis in a java compiler," in *Int'l Conf. Automated Softw. Engineering (ASE)*. IEEE, 2011, pp. 612–615.
- [11] "Available mutation operations (PIT)," <http://pitest.org/quickstart/mutators/>, [Online; accessed 10-August-2016].
- [12] Y.-S. Ma and S.-W. Kim, "Mutation testing cost reduction by clustering overlapped mutants," *J. Systems and Software*, vol. 115, pp. 18–30, 2016.
- [13] S. Hussain, "Mutation clustering," *Ms. Th., Kings College London, Strand, London*, 2008.
- [14] C. Ji, Z. Chen, B. Xu, and Z. Zhao, "A novel method of mutation clustering based on domain analysis." in *SEKE*, vol. 9, 2009, pp. 422–425.
- [15] G. Fraser and A. Arcuri, "Achieving scalable mutation-based generation of whole test suites," *Empirical Software Engineering*, vol. 20, no. 3, pp. 783–812, 2015.
- [16] R. Wille, "Formal concept analysis as mathematical theory of concepts and concept hierarchies," in *Formal concept analysis*. Springer, 2005, pp. 1–33.
- [17] G. Fraser and A. Arcuri, "A large scale evaluation of automated unit test generation using evosuite," *ACM Trans. Softw. Eng. Methodol.*, vol. 24, no. 2, p. 8, 2014.
- [18] S. A. Yevtushenko, "System of data analysis concept explorer," in *Proc. of the national conference on Artificial Intelligence KII*, vol. 2000, 2000.